

Spring Boot Maven Plugin Documentation

Stephane Nicoll, Andy Wilkinson, Scott Frederick

3.0.17.2

Table of Contents

| | |
|---|----|
| 1. Introduction | 1 |
| 2. Getting Started | 2 |
| 3. Using the Plugin | 3 |
| 3.1. Inheriting the Starter Parent POM | 3 |
| 3.2. Using Spring Boot without the Parent POM | 4 |
| 3.3. Overriding settings on the command-line | 5 |
| 4. Goals | 7 |
| 5. Packaging Executable Archives | 8 |
| 5.1. Layered Jar or War | 9 |
| 5.1.1. Custom Layers Configuration | 10 |
| 5.2. <code>spring-boot:repackage</code> | 13 |
| 5.2.1. Required parameters | 13 |
| 5.2.2. Optional parameters | 13 |
| 5.2.3. Parameter details | 14 |
| <code>attach</code> | 14 |
| <code>classifier</code> | 14 |
| <code>embeddedLaunchScript</code> | 15 |
| <code>embeddedLaunchScriptProperties</code> | 15 |
| <code>excludeDevtools</code> | 15 |
| <code>excludeGroupIds</code> | 15 |
| <code>excludes</code> | 16 |
| <code>executable</code> | 16 |
| <code>includeSystemScope</code> | 16 |
| <code>includes</code> | 17 |
| <code>layers</code> | 17 |
| <code>layout</code> | 17 |
| <code>layoutFactory</code> | 18 |
| <code>mainClass</code> | 18 |
| <code>outputDirectory</code> | 18 |
| <code>outputTimestamp</code> | 19 |
| <code>requiresUnpack</code> | 19 |
| <code>skip</code> | 19 |
| 5.3. Examples | 20 |
| 5.3.1. Custom Classifier | 20 |
| 5.3.2. Custom Name | 23 |
| 5.3.3. Local Repackaged Artifact | 24 |
| 5.3.4. Custom Layout | 25 |
| 5.3.5. Dependency Exclusion | 26 |

| | |
|---|----|
| 5.3.6. Layered Archive Tools | 27 |
| 5.3.7. Custom Layers Configuration | 28 |
| 6. Packaging OCI Images | 30 |
| 6.1. Docker Daemon | 30 |
| 6.2. Docker Registry | 31 |
| 6.3. Image Customizations | 32 |
| 6.4. <code>spring-boot:build-image</code> | 34 |
| 6.4.1. Required parameters | 35 |
| 6.4.2. Optional parameters | 35 |
| 6.4.3. Parameter details | 35 |
| <code>classifier</code> | 35 |
| <code>docker</code> | 36 |
| <code>excludeDevtools</code> | 36 |
| <code>excludeGroupIds</code> | 36 |
| <code>excludes</code> | 36 |
| <code>image</code> | 37 |
| <code>includeSystemScope</code> | 37 |
| <code>includes</code> | 37 |
| <code>layers</code> | 38 |
| <code>layout</code> | 38 |
| <code>layoutFactory</code> | 38 |
| <code>mainClass</code> | 39 |
| <code>skip</code> | 39 |
| <code>sourceDirectory</code> | 39 |
| 6.5. <code>spring-boot:build-image-no-fork</code> | 40 |
| 6.5.1. Required parameters | 40 |
| 6.5.2. Optional parameters | 40 |
| 6.5.3. Parameter details | 40 |
| <code>classifier</code> | 40 |
| <code>docker</code> | 41 |
| <code>excludeDevtools</code> | 41 |
| <code>excludeGroupIds</code> | 41 |
| <code>excludes</code> | 42 |
| <code>image</code> | 42 |
| <code>includeSystemScope</code> | 42 |
| <code>includes</code> | 42 |
| <code>layers</code> | 43 |
| <code>layout</code> | 43 |
| <code>layoutFactory</code> | 43 |
| <code>mainClass</code> | 44 |
| <code>skip</code> | 44 |

| | |
|---|----|
| sourceDirectory | 44 |
| 6.6. Examples | 45 |
| 6.6.1. Custom Image Builder | 45 |
| 6.6.2. Builder Configuration | 45 |
| 6.6.3. Runtime JVM Configuration | 46 |
| 6.6.4. Custom Image Name | 47 |
| 6.6.5. Buildpacks | 48 |
| 6.6.6. Image Publishing | 49 |
| 6.6.7. Builder Cache Configuration | 51 |
| 6.6.8. Docker Configuration | 52 |
| Docker Configuration for minikube | 52 |
| Docker Configuration for podman | 53 |
| Docker Configuration for Colima | 54 |
| Docker Configuration for Authentication | 54 |
| 7. Running your Application with Maven | 56 |
| 7.1. spring-boot:run | 57 |
| 7.1.1. Required parameters | 57 |
| 7.1.2. Optional parameters | 57 |
| 7.1.3. Parameter details | 58 |
| addResources | 58 |
| agents | 59 |
| arguments | 59 |
| classesDirectory | 59 |
| commandlineArguments | 59 |
| directories | 60 |
| environmentVariables | 60 |
| excludeGroupIds | 60 |
| excludes | 61 |
| includes | 61 |
| jvmArguments | 61 |
| mainClass | 62 |
| noverify | 62 |
| optimizedLaunch | 62 |
| profiles | 63 |
| skip | 63 |
| systemPropertyVariables | 63 |
| useTestClasspath | 64 |
| workingDirectory | 64 |
| 7.2. Examples | 64 |
| 7.2.1. Debug the Application | 64 |
| 7.2.2. Using System Properties | 65 |

| | |
|--|----|
| 7.2.3. Using Environment Variables | 66 |
| 7.2.4. Using Application Arguments | 67 |
| 7.2.5. Specify Active Profiles | 67 |
| 8. Ahead-of-Time Processing | 69 |
| 8.1. Processing Applications | 69 |
| 8.1.1. Using the Native Profile | 69 |
| 8.2. <code>spring-boot:process-aot</code> | 71 |
| 8.2.1. Required parameters | 71 |
| 8.2.2. Optional parameters | 72 |
| 8.2.3. Parameter details | 72 |
| <code>arguments</code> | 72 |
| <code>classesDirectory</code> | 72 |
| <code>compilerArguments</code> | 73 |
| <code>excludeGroupIds</code> | 73 |
| <code>excludes</code> | 73 |
| <code>generatedClasses</code> | 74 |
| <code>generatedResources</code> | 74 |
| <code>generatedSources</code> | 74 |
| <code>includes</code> | 74 |
| <code>jvmArguments</code> | 75 |
| <code>mainClass</code> | 75 |
| <code>profiles</code> | 75 |
| <code>skip</code> | 76 |
| <code>systemPropertyVariables</code> | 76 |
| 8.3. Processing Tests | 76 |
| 8.4. <code>spring-boot:process-test-aot</code> | 77 |
| 8.4.1. Required parameters | 77 |
| 8.4.2. Optional parameters | 77 |
| 8.4.3. Parameter details | 78 |
| <code>classesDirectory</code> | 78 |
| <code>compilerArguments</code> | 78 |
| <code>excludeGroupIds</code> | 78 |
| <code>excludes</code> | 79 |
| <code>generatedClasses</code> | 79 |
| <code>generatedResources</code> | 79 |
| <code>generatedSources</code> | 80 |
| <code>generatedTestClasses</code> | 80 |
| <code>includes</code> | 80 |
| <code>jvmArguments</code> | 80 |
| <code>skip</code> | 81 |
| <code>systemPropertyVariables</code> | 81 |

| | |
|--|----|
| testClassesDirectory | 81 |
| 9. Running Integration Tests | 83 |
| 9.1. Using Failsafe Without Spring Boot's Parent POM | 83 |
| 9.2. spring-boot:start | 84 |
| 9.2.1. Required parameters | 84 |
| 9.2.2. Optional parameters | 84 |
| 9.2.3. Parameter details | 85 |
| addResources | 85 |
| agents | 85 |
| arguments | 85 |
| classesDirectory | 86 |
| commandlineArguments | 86 |
| directories | 86 |
| environmentVariables | 87 |
| excludeGroupIds | 87 |
| excludes | 87 |
| includes | 88 |
| jmxName | 88 |
| jmxPort | 88 |
| jvmArguments | 89 |
| mainClass | 89 |
| maxAttempts | 89 |
| noverify | 90 |
| profiles | 90 |
| skip | 90 |
| systemPropertyVariables | 91 |
| useTestClasspath | 91 |
| wait | 91 |
| workingDirectory | 91 |
| 9.3. spring-boot:stop | 92 |
| 9.3.1. Optional parameters | 92 |
| 9.3.2. Parameter details | 92 |
| jmxName | 92 |
| jmxPort | 92 |
| skip | 93 |
| 9.4. Examples | 93 |
| 9.4.1. Random Port for Integration Tests | 93 |
| 9.4.2. Customize JMX port | 94 |
| 9.4.3. Skip Integration Tests | 95 |
| 10. Integrating with Actuator | 97 |
| 10.1. spring-boot:build-info | 97 |

| | |
|---|-----|
| 10.1.1. Optional parameters | 98 |
| 10.1.2. Parameter details | 98 |
| additionalProperties | 98 |
| excludeInfoProperties | 98 |
| outputFile | 98 |
| time | 99 |
| 11. Help Information | 100 |
| 11.1. <code>spring-boot:help</code> | 100 |
| 11.1.1. Optional parameters | 100 |
| 11.1.2. Parameter details | 100 |
| detail | 100 |
| goal | 100 |
| indentSize | 101 |
| lineLength | 101 |

Chapter 1. Introduction

The Spring Boot Maven Plugin provides Spring Boot support in [Apache Maven](#). It allows you to package executable jar or war archives, run Spring Boot applications, generate build information and start your Spring Boot application prior to running integration tests.

Chapter 2. Getting Started

To use the Spring Boot Maven Plugin, include the appropriate XML in the `plugins` section of your `pom.xml`, as shown in the following example:

```
<project>
  <modelVersion>4.0.0</modelVersion>
  <artifactId>getting-started</artifactId>
  <!-- ... -->
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
      </plugin>
    </plugins>
  </build>
</project>
```

The plugin is published to the Spring Commercial repository. You will have to configure your build to access this repository. This is usually done through a local artifact repository that mirrors the content of the Spring Commercial repository. Alternatively, while it is not recommended, the Spring Commercial repository can also be accessed directly. In either case, see [the Tanzu Spring Runtime documentation](#) for further details.

Chapter 3. Using the Plugin

Maven users can inherit from the `spring-boot-starter-parent` project to obtain sensible defaults. The parent project provides the following features:

- Java 17 as the default compiler level.
- UTF-8 source encoding.
- Compilation with `-parameters`.
- A dependency management section, inherited from the `spring-boot-dependencies` POM, that manages the versions of common dependencies. This dependency management lets you omit `<version>` tags for those dependencies when used in your own POM.
- An execution of the `repackage` goal with a `repackage` execution id.
- A `native` profile that configures the build to be able to generate a Native image.
- Sensible `resource filtering`.
- Sensible plugin configuration (`Git commit ID`, and `shade`).
- Sensible resource filtering for `application.properties` and `application.yml` including profile-specific files (for example, `application-dev.properties` and `application-dev.yml`)



Since the `application.properties` and `application.yml` files accept Spring style placeholders (`${...}`), the Maven filtering is changed to use `@.>@` placeholders. (You can override that by setting a Maven property called `resource.delimiter`.)

3.1. Inheriting the Starter Parent POM

To configure your project to inherit from the `spring-boot-starter-parent`, set the `parent` as follows:

```
<!-- Inherit defaults from Spring Boot -->
<parent>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-parent</artifactId>
  <version>3.0.17.2</version>
</parent>
```



You should need to specify only the Spring Boot version number on this dependency. If you import additional starters, you can safely omit the version number.

With that setup, you can also override individual dependencies by overriding a property in your own project. For instance, to use a different version of the SLF4J library and the Spring Data release train, you would add the following to your `pom.xml`:

```
<properties>
  <slf4j.version>1.7.30</slf4j.version>
  <spring-data-releasetrain.version>Moore-SR6</spring-data-releasetrain.version>
</properties>
```

Browse the [Dependency versions Appendix](#) in the Spring Boot reference for a complete list of dependency version properties.

3.2. Using Spring Boot without the Parent POM

There may be reasons for you not to inherit from the `spring-boot-starter-parent` POM. You may have your own corporate standard parent that you need to use or you may prefer to explicitly declare all your Maven configuration.

If you do not want to use the `spring-boot-starter-parent`, you can still keep the benefit of the dependency management (but not the plugin management) by using an `import` scoped dependency, as follows:

```
<dependencyManagement>
  <dependencies>
    <dependency>
      <!-- Import dependency management from Spring Boot -->
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-dependencies</artifactId>
      <version>3.0.17.2</version>
      <type>pom</type>
      <scope>import</scope>
    </dependency>
  </dependencies>
</dependencyManagement>
```

The preceding sample setup does not let you override individual dependencies by using properties, as explained above. To achieve the same result, you need to add entries in the `dependencyManagement` section of your project **before** the `spring-boot-dependencies` entry. For instance, to use a different version of the SLF4J library and the Spring Data release train, you could add the following elements to your `pom.xml`:

```

<dependencyManagement>
  <dependencies>
    <!-- Override SLF4J provided by Spring Boot -->
    <dependency>
      <groupId>org.slf4j</groupId>
      <artifactId>slf4j-api</artifactId>
      <version>1.7.30</version>
    </dependency>
    <!-- Override Spring Data release train provided by Spring Boot -->
    <dependency>
      <groupId>org.springframework.data</groupId>
      <artifactId>spring-data-releasetrain</artifactId>
      <version>2020.0.0-SR1</version>
      <type>pom</type>
      <scope>import</scope>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-dependencies</artifactId>
      <version>3.0.17.2</version>
      <type>pom</type>
      <scope>import</scope>
    </dependency>
  </dependencies>
</dependencyManagement>

```

3.3. Overriding settings on the command-line

The plugin offers a number of user properties, starting with `spring-boot`, to let you customize the configuration from the command-line.

For instance, you could tune the profiles to enable when running the application as follows:

```
$ mvn spring-boot:run -Dspring-boot.run.profiles=dev,local
```

If you want to both have a default while allowing it to be overridden on the command-line, you should use a combination of a user-provided project property and MOJO configuration.

```
<project>
  <properties>
    <app.profiles>local,dev</app.profiles>
  </properties>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <profiles>${app.profiles}</profiles>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

The above makes sure that **local** and **dev** are enabled by default. Now a dedicated property has been exposed, this can be overridden on the command-line as well:

```
$ mvn spring-boot:run -Dapp.profiles=test
```

Chapter 4. Goals

The Spring Boot Plugin has the following goals:

| Goal | Description |
|--|--|
| <code>spring-boot:build-image</code> | Package an application into an OCI image using a buildpack, forking the lifecycle to make sure that <code>package</code> ran. This goal is suitable for command-line invocation. If you need to configure a goal <code>execution</code> in your build, use <code>build-image-no-fork</code> instead. |
| <code>spring-boot:build-image-no-fork</code> | Package an application into an OCI image using a buildpack, but without forking the lifecycle. This goal should be used when configuring a goal <code>execution</code> in your build. To invoke the goal on the command-line, use <code>build-image</code> instead. |
| <code>spring-boot:build-info</code> | Generate a <code>build-info.properties</code> file based on the content of the current <code>MavenProject</code> . |
| <code>spring-boot:help</code> | Display help information on <code>spring-boot-maven-plugin</code> . Call <code>mvn spring-boot:help -Ddetail=true -Dgoal=<goal-name></code> to display parameter details. |
| <code>spring-boot:process-aot</code> | Invoke the AOT engine on the application. |
| <code>spring-boot:process-test-aot</code> | Invoke the AOT engine on tests. |
| <code>spring-boot:repackage</code> | Repackage existing JAR and WAR archives so that they can be executed from the command line using <code>java -jar</code> . With <code>layout=NONE</code> can also be used simply to package a JAR with nested dependencies (and no main class, so not executable). |
| <code>spring-boot:run</code> | Run an application in place. |
| <code>spring-boot:start</code> | Start a spring application. Contrary to the <code>run</code> goal, this does not block and allows other goals to operate on the application. This goal is typically used in integration test scenario where the application is started before a test suite and stopped after. |
| <code>spring-boot:stop</code> | Stop an application that has been started by the "start" goal. Typically invoked once a test suite has completed. |

Chapter 5. Packaging Executable Archives

The plugin can create executable archives (jar files and war files) that contain all of an application's dependencies and can then be run with `java -jar`.

Packaging an executable archive is performed by the `repackage` goal, as shown in the following example:

```
<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
      <executions>
        <execution>
          <goals>
            <goal>repackage</goal>
          </goals>
        </execution>
      </executions>
    </plugin>
  </plugins>
</build>
```



If you are using `spring-boot-starter-parent`, such execution is already pre-configured with a `repackage` execution ID so that only the plugin definition should be added.

The example above repackages a `jar` or `war` archive that is built during the package phase of the Maven lifecycle, including any `provided` dependencies that are defined in the project. If some of these dependencies need to be excluded, you can use one of the `exclude` options; see the [dependency exclusion](#) for more details.

The original (that is non-executable) artifact is renamed to `.original` by default but it is also possible to keep the original artifact using a custom classifier.



The `outputFileNameMapping` feature of the `maven-war-plugin` is currently not supported.

Devtools is automatically excluded by default (you can control that using the `excludeDevtools` property). In order to make that work with `war` packaging, the `spring-boot-devtools` dependency must be set as `optional` or with the `provided` scope.

The plugin rewrites your manifest, and in particular it manages the `Main-Class` and `Start-Class` entries. If the defaults don't work you have to configure the values in the Spring Boot plugin, not in the jar plugin. The `Main-Class` in the manifest is controlled by the `layout` property of the Spring Boot plugin, as shown in the following example:

```

<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
      <configuration>
        <mainClass>${start.class}</mainClass>
        <layout>ZIP</layout>
      </configuration>
      <executions>
        <execution>
          <goals>
            <goal>repackage</goal>
          </goals>
        </execution>
      </executions>
    </plugin>
  </plugins>
</build>

```

The `layout` property defaults to a value determined by the archive type (`jar` or `war`). The following layouts are available:

- **JAR**: regular executable JAR layout.
- **WAR**: executable WAR layout. `provided` dependencies are placed in `WEB-INF/lib-provided` to avoid any clash when the `war` is deployed in a servlet container.
- **ZIP** (alias to **DIR**): similar to the **JAR** layout using `PropertiesLauncher`.
- **NONE**: Bundle all dependencies and project resources. Does not bundle a bootstrap loader.

5.1. Layered Jar or War

A repackaged jar contains the application's classes and dependencies in `BOOT-INF/classes` and `BOOT-INF/lib` respectively. Similarly, an executable war contains the application's classes in `WEB-INF/classes` and dependencies in `WEB-INF/lib` and `WEB-INF/lib-provided`. For cases where a docker image needs to be built from the contents of a jar or war, it's useful to be able to separate these directories further so that they can be written into distinct layers.

Layered archives use the same layout as a regular repackaged jar or war, but include an additional meta-data file that describes each layer.

By default, the following layers are defined:

- `dependencies` for any dependency whose version does not contain `SNAPSHOT`.
- `spring-boot-loader` for the loader classes.
- `snapshot-dependencies` for any dependency whose version contains `SNAPSHOT`.
- `application` for local module dependencies, application classes, and resources.

Module dependencies are identified by looking at all of the modules that are part of the current build. If a module dependency can only be resolved because it has been installed into Maven's local cache and it is not part of the current build, it will be identified as regular dependency.

The layers order is important as it determines how likely previous layers can be cached when part of the application changes. The default order is `dependencies`, `spring-boot-loader`, `snapshot-dependencies`, `application`. Content that is least likely to change should be added first, followed by layers that are more likely to change.

The repackaged archive includes the `layers.idx` file by default. To disable this feature, you can do so in the following manner:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <layers>
            <enabled>>false</enabled>
          </layers>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

5.1.1. Custom Layers Configuration

Depending on your application, you may want to tune how layers are created and add new ones. This can be done using a separate configuration file that should be registered as shown below:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <layers>
            <enabled>true</enabled>
          </layers>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

The configuration file describes how an archive can be separated into layers, and the order of those layers. The following example shows how the default ordering described above can be defined explicitly:

```

<layers xmlns="http://www.springframework.org/schema/boot/layers"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.springframework.org/schema/boot/layers
    https://www.springframework.org/schema/boot/layers/layers-
3.0.xsd">
  <application>
    <into layer="spring-boot-loader">
      <include>org/springframework/boot/loader/**</include>
    </into>
    <into layer="application" />
  </application>
  <dependencies>
    <into layer="application">
      <includeModuleDependencies />
    </into>
    <into layer="snapshot-dependencies">
      <include>*:*:*SNAPSHOT</include>
    </into>
    <into layer="dependencies" />
  </dependencies>
  <layerOrder>
    <layer>dependencies</layer>
    <layer>spring-boot-loader</layer>
    <layer>snapshot-dependencies</layer>
    <layer>application</layer>
  </layerOrder>
</layers>

```

The `layers` XML format is defined in three sections:

- The `<application>` block defines how the application classes and resources should be layered.
- The `<dependencies>` block defines how dependencies should be layered.
- The `<layerOrder>` block defines the order that the layers should be written.

Nested `<into>` blocks are used within `<application>` and `<dependencies>` sections to claim content for a layer. The blocks are evaluated in the order that they are defined, from top to bottom. Any content not claimed by an earlier block remains available for subsequent blocks to consider.

The `<into>` block claims content using nested `<include>` and `<exclude>` elements. The `<application>` section uses Ant-style path matching for include/exclude expressions. The `<dependencies>` section uses `group:artifact[:version]` patterns. It also provides `<includeModuleDependencies />` and `<excludeModuleDependencies />` elements that can be used to include or exclude local module dependencies.

If no `<include>` is defined, then all content (not claimed by an earlier block) is considered.

If no `<exclude>` is defined, then no exclusions are applied.

Looking at the `<dependencies>` example above, we can see that the first `<into>` will claim all module

dependencies for the `application.layer`. The next `<into>` will claim all SNAPSHOT dependencies for the `snapshot-dependencies` layer. The final `<into>` will claim anything left (in this case, any dependency that is not a SNAPSHOT) for the `dependencies` layer.

The `<application>` block has similar rules. First claiming `org/springframework/boot/loader/**` content for the `spring-boot-loader` layer. Then claiming any remaining classes and resources for the `application` layer.



The order that `<into>` blocks are defined is often different from the order that the layers are written. For this reason the `<layerOrder>` element must always be included and *must* cover all layers referenced by the `<into>` blocks.

5.2. spring-boot:repackage

`org.springframework.boot:spring-boot-maven-plugin:3.0.17.2`

Repackage existing JAR and WAR archives so that they can be executed from the command line using `java -jar`. With `layout=NONE` can also be used simply to package a JAR with nested dependencies (and no main class, so not executable).

5.2.1. Required parameters

| Name | Type | Default |
|------------------------------|------|--|
| <code>outputDirectory</code> | File | <code>\${project.build.directory}</code> |

5.2.2. Optional parameters

| Name | Type | Default |
|---|---------------|---------|
| <code>attach</code> | boolean | true |
| <code>classifier</code> | String | |
| <code>embeddedLaunchScript</code> | File | |
| <code>embeddedLaunchScriptProperties</code> | Properties | |
| <code>excludeDevtools</code> | boolean | true |
| <code>excludeGroupIds</code> | String | |
| <code>excludes</code> | List | |
| <code>executable</code> | boolean | false |
| <code>includeSystemScope</code> | boolean | false |
| <code>includes</code> | List | |
| <code>layers</code> | Layers | |
| <code>layout</code> | LayoutType | |
| <code>layoutFactory</code> | LayoutFactory | |
| <code>mainClass</code> | String | |

| Name | Type | Default |
|------------------------------|---------|--|
| <code>outputTimestamp</code> | String | <code>\${project.build.outputTimestamp}</code> |
| <code>requiresUnpack</code> | List | |
| <code>skip</code> | boolean | <code>false</code> |

5.2.3. Parameter details

`attach`

Attach the repackaged archive to be installed into your local Maven repository or deployed to a remote repository. If no classifier has been configured, it will replace the normal jar. If a `classifier` has been configured such that the normal jar and the repackaged jar are different, it will be attached alongside the normal jar. When the property is set to `false`, the repackaged archive will not be installed or deployed.

| | |
|----------------------|---------------------|
| Name | <code>attach</code> |
| Type | boolean |
| Default value | <code>true</code> |
| User property | |
| Since | <code>1.4.0</code> |

`classifier`

Classifier to add to the repackaged archive. If not given, the main artifact will be replaced by the repackaged archive. If given, the classifier will also be used to determine the source archive to repackage: if an artifact with that classifier already exists, it will be used as source and replaced. If no such artifact exists, the main artifact will be used as source and the repackaged archive will be attached as a supplemental artifact with that classifier. Attaching the artifact allows to deploy it alongside to the original one, see [the Maven documentation for more details](#).

| | |
|----------------------|-------------------------------|
| Name | <code>classifier</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | |
| Since | <code>1.0.0</code> |

embeddedLaunchScript

The embedded launch script to prepend to the front of the jar if it is fully executable. If not specified the 'Spring Boot' default script will be used.

| | |
|----------------------|----------------------|
| Name | embeddedLaunchScript |
| Type | java.io.File |
| Default value | |
| User property | |
| Since | 1.3.0 |

embeddedLaunchScriptProperties

Properties that should be expanded in the embedded launch script.

| | |
|----------------------|--------------------------------|
| Name | embeddedLaunchScriptProperties |
| Type | java.util.Properties |
| Default value | |
| User property | |
| Since | 1.3.0 |

excludeDevtools

Exclude Spring Boot devtools from the repackaged archive.

| | |
|----------------------|---------------------------------------|
| Name | excludeDevtools |
| Type | boolean |
| Default value | true |
| User property | spring-boot.repackage.excludeDevtools |
| Since | 1.3.0 |

excludeGroupIds

Comma separated list of groupId names to exclude (exact match).

| | |
|-------------|-----------------|
| Name | excludeGroupIds |
|-------------|-----------------|

| | |
|----------------------|--|
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | <code>spring-boot.excludeGroupIds</code> |
| Since | <code>1.1.0</code> |

`excludes`

Collection of artifact definitions to exclude. The `Exclude` element defines mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|----------------------|-----------------------------------|
| Name | <code>excludes</code> |
| Type | <code>java.util.List</code> |
| Default value | |
| User property | <code>spring-boot.excludes</code> |
| Since | <code>1.1.0</code> |

`executable`

Make a fully executable jar for *nix machines by prepending a launch script to the jar. <p>Currently, some tools do not accept this format so you may not always be able to use this technique. For example, `jar -xf` may silently fail to extract a jar or war that has been made fully-executable. It is recommended that you only enable this option if you intend to execute it directly, rather than running it with `java -jar` or deploying it to a servlet container.

| | |
|----------------------|-------------------------|
| Name | <code>executable</code> |
| Type | <code>boolean</code> |
| Default value | <code>false</code> |
| User property | |
| Since | <code>1.3.0</code> |

`includeSystemScope`

Include system scoped dependencies.

| | |
|-------------|---------------------------------|
| Name | <code>includeSystemScope</code> |
|-------------|---------------------------------|

| | |
|----------------------|---------|
| Type | boolean |
| Default value | false |
| User property | |
| Since | 1.4.0 |

includes

Collection of artifact definitions to include. The `Include` element defines mandatory `groupId` and `artifactId` properties and an optional mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|----------------------|----------------------|
| Name | includes |
| Type | java.util.List |
| Default value | |
| User property | spring-boot.includes |
| Since | 1.2.0 |

layers

Layer configuration with options to disable layer creation, exclude layer tools jar, and provide a custom layers configuration file.

| | |
|----------------------|---------------------------------------|
| Name | layers |
| Type | org.springframework.boot.maven.Layers |
| Default value | |
| User property | |
| Since | 2.3.0 |

layout

The type of archive (which corresponds to how the dependencies are laid out inside it). Possible values are `JAR`, `WAR`, `ZIP`, `DIR`, `NONE`. Defaults to a guess based on the archive type.

| | |
|-------------|---|
| Name | layout |
| Type | org.springframework.boot.maven.AbstractPackagerMojo\$LayoutType |

| | |
|----------------------|---|
| Default value | |
| User property | <code>spring-boot.repackage.layout</code> |
| Since | <code>1.0.0</code> |

layoutFactory

The layout factory that will be used to create the executable archive if no explicit layout is set. Alternative layouts implementations can be provided by 3rd parties.

| | |
|----------------------|--|
| Name | <code>layoutFactory</code> |
| Type | <code>org.springframework.boot.loader.tools.LayoutFactory</code> |
| Default value | |
| User property | |
| Since | <code>1.5.0</code> |

mainClass

The name of the main class. If not specified the first compiled class found that contains a `main` method will be used.

| | |
|----------------------|-------------------------------|
| Name | <code>mainClass</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | |
| Since | <code>1.0.0</code> |

outputDirectory

Directory containing the generated archive.

| | |
|----------------------|--|
| Name | <code>outputDirectory</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.directory}</code> |

| | |
|----------------------|-------|
| User property | |
| Since | 1.0.0 |

outputTimestamp

Timestamp for reproducible output archive entries, either formatted as ISO 8601 (yyyy-MM-ddT^THH:mm:ssXXX) or an `int` representing seconds since the epoch.

| | |
|----------------------|-----------------------------------|
| Name | outputTimestamp |
| Type | java.lang.String |
| Default value | \${project.build.outputTimestamp} |
| User property | |
| Since | 2.3.0 |

requiresUnpack

A list of the libraries that must be unpacked from fat jars in order to run. Specify each library as a `<dependency>` with a `<groupId>` and a `<artifactId>` and they will be unpacked at runtime.

| | |
|----------------------|----------------|
| Name | requiresUnpack |
| Type | java.util.List |
| Default value | |
| User property | |
| Since | 1.1.0 |

skip

Skip the execution.

| | |
|----------------------|----------------------------|
| Name | skip |
| Type | boolean |
| Default value | false |
| User property | spring-boot.repackage.skip |

| | |
|-------|-------|
| Since | 1.2.0 |
|-------|-------|

5.3. Examples

5.3.1. Custom Classifier

By default, the `repackage` goal replaces the original artifact with the repackaged one. That is a sane behavior for modules that represent an application but if your module is used as a dependency of another module, you need to provide a classifier for the repackaged one. The reason for that is that application classes are packaged in `BOOT-INF/classes` so that the dependent module cannot load a repackaged jar's classes.

If that is the case or if you prefer to keep the original artifact and attach the repackaged one with a different classifier, configure the plugin as shown in the following example:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <executions>
          <execution>
            <id>repackage</id>
            <goals>
              <goal>repackage</goal>
            </goals>
            <configuration>
              <classifier>exec</classifier>
            </configuration>
          </execution>
        </executions>
      </plugin>
    </plugins>
  </build>
</project>
```

If you are using `spring-boot-starter-parent`, the `repackage` goal is executed automatically in an execution with id `repackage`. In that setup, only the configuration should be specified, as shown in the following example:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <executions>
          <execution>
            <id>repackage</id>
            <configuration>
              <classifier>exec</classifier>
            </configuration>
          </execution>
        </executions>
      </plugin>
    </plugins>
  </build>
</project>
```

This configuration will generate two artifacts: the original one and the repackaged counter part produced by the repackage goal. Both will be installed/deployed transparently.

You can also use the same configuration if you want to repackage a secondary artifact the same way the main artifact is replaced. The following configuration installs/deploys a single **task** classified artifact with the repackaged application:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId>
        <artifactId>maven-jar-plugin</artifactId>
        <executions>
          <execution>
            <goals>
              <goal>jar</goal>
            </goals>
            <phase>package</phase>
            <configuration>
              <classifier>task</classifier>
            </configuration>
          </execution>
        </executions>
      </plugin>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <executions>
          <execution>
            <id>repackage</id>
            <goals>
              <goal>repackage</goal>
            </goals>
            <configuration>
              <classifier>task</classifier>
            </configuration>
          </execution>
        </executions>
      </plugin>
    </plugins>
  </build>
</project>

```

As both the `maven-jar-plugin` and the `spring-boot-maven-plugin` runs at the same phase, it is important that the jar plugin is defined first (so that it runs before the repackage goal). Again, if you are using `spring-boot-starter-parent`, this can be simplified as follows:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId>
        <artifactId>maven-jar-plugin</artifactId>
        <executions>
          <execution>
            <id>default-jar</id>
            <configuration>
              <classifier>task</classifier>
            </configuration>
          </execution>
        </executions>
      </plugin>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <executions>
          <execution>
            <id>repackage</id>
            <configuration>
              <classifier>task</classifier>
            </configuration>
          </execution>
        </executions>
      </plugin>
    </plugins>
  </build>
</project>

```

5.3.2. Custom Name

If you need the repackaged jar to have a different local name than the one defined by the `artifactId` attribute of the project, use the standard `finalName`, as shown in the following example:

```
<project>
  <build>
    <finalName>my-app</finalName>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <executions>
          <execution>
            <id>repackage</id>
            <goals>
              <goal>repackage</goal>
            </goals>
          </execution>
        </executions>
      </plugin>
    </plugins>
  </build>
</project>
```

This configuration will generate the repackaged artifact in `target/my-app.jar`.

5.3.3. Local Repackaged Artifact

By default, the `repackage` goal replaces the original artifact with the executable one. If you need to only deploy the original jar and yet be able to run your app with the regular file name, configure the plugin as follows:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <executions>
          <execution>
            <id>repackage</id>
            <goals>
              <goal>repackage</goal>
            </goals>
            <configuration>
              <attach>>false</attach>
            </configuration>
          </execution>
        </executions>
      </plugin>
    </plugins>
  </build>
</project>
```

This configuration generates two artifacts: the original one and the executable counter part produced by the `repackage` goal. Only the original one will be installed/deployed.

5.3.4. Custom Layout

Spring Boot repackages the jar file for this project using a custom layout factory defined in the additional jar file, provided as a dependency to the build plugin:


```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <executions>
          <execution>
            <id>repackage</id>
            <goals>
              <goal>repackage</goal>
            </goals>
            <configuration>
              <layoutFactory
implementation="com.example.CustomLayoutFactory">
                <customProperty>value</customProperty>
              </layoutFactory>
            </configuration>
          </execution>
        </executions>
        <dependencies>
          <dependency>
            <groupId>com.example</groupId>
            <artifactId>custom-layout</artifactId>
            <version>0.0.1.BUILD-SNAPSHOT</version>
          </dependency>
        </dependencies>
      </plugin>
    </plugins>
  </build>
</project>

```

The layout factory is provided as an implementation of `LayoutFactory` (from `spring-boot-loader-tools`) explicitly specified in the pom. If there is only one custom `LayoutFactory` on the plugin classpath and it is listed in `META-INF/spring.factories` then it is unnecessary to explicitly set it in the plugin configuration.

Layout factories are always ignored if an explicit `layout` is set.

5.3.5. Dependency Exclusion

By default, both the `repackage` and the `run` goals will include any `provided` dependencies that are defined in the project. A Spring Boot project should consider `provided` dependencies as "container" dependencies that are required to run the application. Generally speaking, Spring Boot projects are not used as dependencies and are therefore unlikely to have any `optional` dependencies. When a project does have optional dependencies they too will be included by the `repackage` and `run` goals.

Some of these dependencies may not be required at all and should be excluded from the executable jar. For consistency, they should not be present either when running the application.

There are two ways one can exclude a dependency from being packaged/used at runtime:

- Exclude a specific artifact identified by `groupId` and `artifactId`, optionally with a `classifier` if needed.
- Exclude any artifact belonging to a given `groupId`.

The following example excludes `com.example:module1`, and only that artifact:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <excludes>
            <exclude>
              <groupId>com.example</groupId>
              <artifactId>module1</artifactId>
            </exclude>
          </excludes>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

This example excludes any artifact belonging to the `com.example` group:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <excludeGroupIds>com.example</excludeGroupIds>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

5.3.6. Layered Archive Tools

When a layered jar or war is created, the `spring-boot-jarmode-layertools` jar will be added as a dependency to your archive. With this jar on the classpath, you can launch your application in a special mode which allows the bootstrap code to run something entirely different from your

application, for example, something that extracts the layers. If you wish to exclude this dependency, you can do so in the following manner:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <layers>
            <includeLayerTools>>false</includeLayerTools>
          </layers>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

5.3.7. Custom Layers Configuration

The default setup splits dependencies into snapshot and non-snapshot, however, you may have more complex rules. For example, you may want to isolate company-specific dependencies of your project in a dedicated layer. The following `layers.xml` configuration shown one such setup:

```

<layers xmlns="http://www.springframework.org/schema/boot/layers"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.springframework.org/schema/boot/layers
    https://www.springframework.org/schema/boot/layers/layers-
3.0.xsd">
  <application>
    <into layer="spring-boot-loader">
      <include>org/springframework/boot/loader/**</include>
    </into>
    <into layer="application" />
  </application>
  <dependencies>
    <into layer="snapshot-dependencies">
      <include>*:*:*SNAPSHOT</include>
    </into>
    <into layer="company-dependencies">
      <include>com.acme:*</include>
    </into>
    <into layer="dependencies"/>
  </dependencies>
  <layerOrder>
    <layer>dependencies</layer>
    <layer>spring-boot-loader</layer>
    <layer>snapshot-dependencies</layer>
    <layer>company-dependencies</layer>
    <layer>application</layer>
  </layerOrder>
</layers>

```

The configuration above creates an additional **company-dependencies** layer with all libraries with the **com.acme** groupId.

Chapter 6. Packaging OCI Images

The plugin can create an [OCI image](#) from a jar or war file using [Cloud Native Buildpacks](#) (CNB). Images can be built on the command-line using the `build-image` goal. This makes sure that the package lifecycle has run before the image is created.



For security reasons, images build and run as non-root users. See the [CNB specification](#) for more details.

The easiest way to get started is to invoke `mvn spring-boot:build-image` on a project. It is possible to automate the creation of an image whenever the `package` phase is invoked, as shown in the following example:

```
<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
      <executions>
        <execution>
          <goals>
            <goal>build-image-no-fork</goal>
          </goals>
        </execution>
      </executions>
    </plugin>
  </plugins>
</build>
```



Use `build-image-no-fork` when binding the goal to the package lifecycle. This goal is similar to `build-image` but does not fork the lifecycle to make sure `package` has run. In the rest of this section, `build-image` is used to refer to either the `build-image` or `build-image-no-fork` goals.



While the buildpack runs from an [executable archive](#), it is not necessary to execute the `repackage` goal first as the executable archive is created automatically if necessary. When the `build-image` repackages the application, it applies the same settings as the `repackage` goal would, that is dependencies can be excluded using one of the exclude options, and Devtools is automatically excluded by default (you can control that using the `excludeDevtools` property).

6.1. Docker Daemon

The `build-image` goal requires access to a Docker daemon. By default, it will communicate with a Docker daemon over a local connection. This works with [Docker Engine](#) on all supported platforms without configuration.

Environment variables can be set to configure the `build-image` goal to use an alternative local or remote connection. The following table shows the environment variables and their values:

| Environment variable | Description |
|--------------------------------|--|
| <code>DOCKER_HOST</code> | URL containing the host and port for the Docker daemon - for example <code>tcp://192.168.99.100:2376</code> |
| <code>DOCKER_TLS_VERIFY</code> | Enable secure HTTPS protocol when set to <code>1</code> (optional) |
| <code>DOCKER_CERT_PATH</code> | Path to certificate and key files for HTTPS (required if <code>DOCKER_TLS_VERIFY=1</code> , ignored otherwise) |

Docker daemon connection information can also be provided using `docker` parameters in the plugin configuration. The following table summarizes the available parameters:

| Parameter | Description |
|--------------------------------|---|
| <code>host</code> | URL containing the host and port for the Docker daemon - for example <code>tcp://192.168.99.100:2376</code> |
| <code>tlsVerify</code> | Enable secure HTTPS protocol when set to <code>true</code> (optional) |
| <code>certPath</code> | Path to certificate and key files for HTTPS (required if <code>tlsVerify</code> is <code>true</code> , ignored otherwise) |
| <code>bindHostToBuilder</code> | When <code>true</code> , the value of the <code>host</code> property will be provided to the container that is created for the CNB builder (optional) |

For more details, see also [examples](#).

6.2. Docker Registry

If the Docker images specified by the `builder` or `runImage` parameters are stored in a private Docker image registry that requires authentication, the authentication credentials can be provided using `docker.builderRegistry` parameters.

If the generated Docker image is to be published to a Docker image registry, the authentication credentials can be provided using `docker.publishRegistry` parameters.

Parameters are provided for user authentication or identity token authentication. Consult the documentation for the Docker registry being used to store images for further information on supported authentication methods.

The following table summarizes the available parameters for `docker.builderRegistry` and `docker.publishRegistry`:

| Parameter | Description |
|-----------------------|---|
| <code>username</code> | Username for the Docker image registry user. Required for user authentication. |
| <code>password</code> | Password for the Docker image registry user. Required for user authentication. |
| <code>url</code> | Address of the Docker image registry. Optional for user authentication. |
| <code>email</code> | E-mail address for the Docker image registry user. Optional for user authentication. |
| <code>token</code> | Identity token for the Docker image registry user. Required for token authentication. |

For more details, see also [examples](#).

6.3. Image Customizations

The plugin invokes a [builder](#) to orchestrate the generation of an image. The builder includes multiple [buildpacks](#) that can inspect the application to influence the generated image. By default, the plugin chooses a builder image. The name of the generated image is deduced from project properties.

The `image` parameter allows configuration of the builder and how it should operate on the project. The following table summarizes the available parameters and their default values:

| Parameter / (User Property) | Description | Default value |
|--|---|--|
| <code>builder</code> (spring-boot.build-image.builder) | Name of the Builder image to use. | <code>paketobuildpacks/builder-jammy-base:latest</code> |
| <code>runImage</code> (spring-boot.build-image.runImage) | Name of the run image to use. | No default value, indicating the run image specified in Builder metadata should be used. |
| <code>name</code> (spring-boot.build-image.imageName) | Image name for the generated image. | <code>docker.io/library/\${project.artifactId}:\${project.version}</code> |

| Parameter / (User Property) | Description | Default value |
|--|--|--|
| <code>pullPolicy</code> (spring-boot-build-image.pullPolicy) | Policy used to determine when to pull the builder and run images from the registry. Acceptable values are ALWAYS , NEVER , and IF_NOT_PRESENT . | ALWAYS |
| <code>env</code> | Environment variables that should be passed to the builder. | |
| <code>buildpacks</code> | Buildpacks that the builder should use when building the image. Only the specified buildpacks will be used, overriding the default buildpacks included in the builder. Buildpack references must be in one of the following forms: <ul style="list-style-type: none"> • Buildpack in the builder - <code>[urn:cnb:builder:]<buildpack ID>[@<version>]</code> • Buildpack in a directory on the file system - <code>[file://]<path></code> • Buildpack in a gzipped tar (.tgz) file on the file system - <code>[file://]<path>/<file name></code> • Buildpack in an OCI image - <code>[docker://]<host>/<repo>[:<tag>][@<digest>]</code> | None, indicating the builder should use the buildpacks included in it. |
| <code>bindings</code> | Volume bind mounts that should be mounted to the builder container when building the image. The bindings will be passed unparsed and unvalidated to Docker when creating the builder container. Bindings must be in one of the following forms: <ul style="list-style-type: none"> • <code><host source path>:<container destination path>[:<options>]</code> • <code><host volume name>:<container destination path>[:<options>]</code> <p>Where <code><options></code> can contain:</p> <ul style="list-style-type: none"> • <code>ro</code> to mount the volume as read-only in the container • <code>rw</code> to mount the volume as readable and writable in the container • <code>volume-opt=key=value</code> to specify key-value pairs consisting of an option name and its value | |
| <code>network +</code> (spring-boot-build-image.network) | The network driver the builder container will be configured to use. The value supplied will be passed unvalidated to Docker when creating the builder container. | |

| Parameter / (User Property) | Description | Default value |
|--|---|---|
| <code>cleanCache</code> + (spring-boot-build-image.cleanCache) | Whether to clean the cache before building. | <code>false</code> |
| <code>verboseLogging</code> | Enables verbose logging of builder operations. | <code>false</code> |
| <code>publish</code> + (spring-boot-build-image.publish) | Whether to publish the generated image to a Docker registry. | <code>false</code> |
| <code>tags</code> | One or more additional tags to apply to the generated image. The values provided to the <code>tags</code> option should be full image references in the form of <code>[image name]:[tag]</code> or <code>[repository]/[image name]:[tag]</code> . | |
| <code>buildCache</code> | A cache containing layers created by buildpacks and used by the image building process. | A named volume in the Docker daemon, with a name derived from the image name. |
| <code>launchCache</code> | A cache containing layers created by buildpacks and used by the image launching process. | A named volume in the Docker daemon, with a name derived from the image name. |



The plugin detects the target Java compatibility of the project using the compiler's plugin configuration or the `maven.compiler.target` property. When using the default Paketo builder and buildpacks, the plugin instructs the buildpacks to install the same Java version. You can override this behaviour as shown in the [builder configuration](#) examples.

For more details, see also [examples](#).

6.4. spring-boot:build-image

`org.springframework.boot:spring-boot-maven-plugin:3.0.17.2`

Package an application into an OCI image using a buildpack, forking the lifecycle to make sure that `package` ran. This goal is suitable for command-line invocation. If you need to configure a goal

`execution` in your build, use `build-image-no-fork` instead.

6.4.1. Required parameters

| Name | Type | Default |
|------------------------------|------|--|
| <code>sourceDirectory</code> | File | <code>\${project.build.directory}</code> |

6.4.2. Optional parameters

| Name | Type | Default |
|---------------------------------|---------------|--------------------|
| <code>classifier</code> | String | |
| <code>docker</code> | Docker | |
| <code>excludeDevtools</code> | boolean | <code>true</code> |
| <code>excludeGroupIds</code> | String | |
| <code>excludes</code> | List | |
| <code>image</code> | Image | |
| <code>includeSystemScope</code> | boolean | <code>false</code> |
| <code>includes</code> | List | |
| <code>layers</code> | Layers | |
| <code>layout</code> | LayoutType | |
| <code>layoutFactory</code> | LayoutFactory | |
| <code>mainClass</code> | String | |
| <code>skip</code> | boolean | <code>false</code> |

6.4.3. Parameter details

`classifier`

Classifier used when finding the source archive.

| | |
|----------------------|-------------------------------|
| Name | <code>classifier</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | |
| Since | <code>2.3.0</code> |

docker

Docker configuration options.

| | |
|----------------------|---------------------------------------|
| Name | docker |
| Type | org.springframework.boot.maven.Docker |
| Default value | |
| User property | |
| Since | 2.4.0 |

excludeDevtools

Exclude Spring Boot devtools from the repackaged archive.

| | |
|----------------------|---------------------------------------|
| Name | excludeDevtools |
| Type | boolean |
| Default value | true |
| User property | spring-boot.repackage.excludeDevtools |
| Since | 1.3.0 |

excludeGroupIds

Comma separated list of groupId names to exclude (exact match).

| | |
|----------------------|-----------------------------|
| Name | excludeGroupIds |
| Type | java.lang.String |
| Default value | |
| User property | spring-boot.excludeGroupIds |
| Since | 1.1.0 |

excludes

Collection of artifact definitions to exclude. The `Exclude` element defines mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|-------------|----------|
| Name | excludes |
|-------------|----------|

| | |
|----------------------|----------------------|
| Type | java.util.List |
| Default value | |
| User property | spring-boot.excludes |
| Since | 1.1.0 |

image

Image configuration, with `builder`, `runImage`, `name`, `env`, `cleanCache`, `verboseLogging`, `pullPolicy`, and `publish` options.

| | |
|----------------------|--------------------------------------|
| Name | image |
| Type | org.springframework.boot.maven.Image |
| Default value | |
| User property | |
| Since | 2.3.0 |

includeSystemScope

Include system scoped dependencies.

| | |
|----------------------|--------------------|
| Name | includeSystemScope |
| Type | boolean |
| Default value | false |
| User property | |
| Since | 1.4.0 |

includes

Collection of artifact definitions to include. The `Include` element defines mandatory `groupId` and `artifactId` properties and an optional mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|-------------|----------------|
| Name | includes |
| Type | java.util.List |

| | |
|----------------------|-----------------------------------|
| Default value | |
| User property | <code>spring-boot.includes</code> |
| Since | 1.2.0 |

layers

Layer configuration with options to disable layer creation, exclude layer tools jar, and provide a custom layers configuration file.

| | |
|----------------------|--|
| Name | <code>layers</code> |
| Type | <code>org.springframework.boot.maven.Layers</code> |
| Default value | |
| User property | |
| Since | 2.3.0 |

layout

The type of archive (which corresponds to how the dependencies are laid out inside it). Possible values are `JAR`, `WAR`, `ZIP`, `DIR`, `NONE`. Defaults to a guess based on the archive type.

| | |
|----------------------|--|
| Name | <code>layout</code> |
| Type | <code>org.springframework.boot.maven.AbstractPackagerMojo\$LayoutType</code> |
| Default value | |
| User property | |
| Since | 2.3.11 |

layoutFactory

The layout factory that will be used to create the executable archive if no explicit layout is set. Alternative layouts implementations can be provided by 3rd parties.

| | |
|----------------------|--|
| Name | <code>layoutFactory</code> |
| Type | <code>org.springframework.boot.loader.tools.LayoutFactory</code> |
| Default value | |

| | |
|----------------------|--------|
| User property | |
| Since | 2.3.11 |

mainClass

The name of the main class. If not specified the first compiled class found that contains a `main` method will be used.

| | |
|----------------------|------------------|
| Name | mainClass |
| Type | java.lang.String |
| Default value | |
| User property | |
| Since | 1.0.0 |

skip

Skip the execution.

| | |
|----------------------|------------------------------|
| Name | skip |
| Type | boolean |
| Default value | false |
| User property | spring-boot.build-image.skip |
| Since | 2.3.0 |

sourceDirectory

Directory containing the source archive.

| | |
|----------------------|-----------------------------|
| Name | sourceDirectory |
| Type | java.io.File |
| Default value | \${project.build.directory} |
| User property | |
| Since | 2.3.0 |

6.5. spring-boot:build-image-no-fork

org.springframework.boot:spring-boot-maven-plugin:3.0.17.2

Package an application into an OCI image using a buildpack, but without forking the lifecycle. This goal should be used when configuring a goal `execution` in your build. To invoke the goal on the command-line, use `build-image` instead.

6.5.1. Required parameters

| Name | Type | Default |
|------------------------------|-------------------|--|
| <code>sourceDirectory</code> | <code>File</code> | <code>\${project.build.directory}</code> |

6.5.2. Optional parameters

| Name | Type | Default |
|---------------------------------|----------------------------|--------------------|
| <code>classifier</code> | <code>String</code> | |
| <code>docker</code> | <code>Docker</code> | |
| <code>excludeDevtools</code> | <code>boolean</code> | <code>true</code> |
| <code>excludeGroupIds</code> | <code>String</code> | |
| <code>excludes</code> | <code>List</code> | |
| <code>image</code> | <code>Image</code> | |
| <code>includeSystemScope</code> | <code>boolean</code> | <code>false</code> |
| <code>includes</code> | <code>List</code> | |
| <code>layers</code> | <code>Layers</code> | |
| <code>layout</code> | <code>LayoutType</code> | |
| <code>layoutFactory</code> | <code>LayoutFactory</code> | |
| <code>mainClass</code> | <code>String</code> | |
| <code>skip</code> | <code>boolean</code> | <code>false</code> |

6.5.3. Parameter details

`classifier`

Classifier used when finding the source archive.

| | |
|----------------------|-------------------------------|
| Name | <code>classifier</code> |
| Type | <code>java.lang.String</code> |
| Default value | |

| | |
|----------------------|-------|
| User property | |
| Since | 2.3.0 |

docker

Docker configuration options.

| | |
|----------------------|---------------------------------------|
| Name | docker |
| Type | org.springframework.boot.maven.Docker |
| Default value | |
| User property | |
| Since | 2.4.0 |

excludeDevtools

Exclude Spring Boot devtools from the repackaged archive.

| | |
|----------------------|---------------------------------------|
| Name | excludeDevtools |
| Type | boolean |
| Default value | true |
| User property | spring-boot.repackage.excludeDevtools |
| Since | 1.3.0 |

excludeGroupIds

Comma separated list of groupId names to exclude (exact match).

| | |
|----------------------|-----------------------------|
| Name | excludeGroupIds |
| Type | java.lang.String |
| Default value | |
| User property | spring-boot.excludeGroupIds |
| Since | 1.1.0 |

excludes

Collection of artifact definitions to exclude. The `Exclude` element defines mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|----------------------|----------------------|
| Name | excludes |
| Type | java.util.List |
| Default value | |
| User property | spring-boot.excludes |
| Since | 1.1.0 |

image

Image configuration, with `builder`, `runImage`, `name`, `env`, `cleanCache`, `verboseLogging`, `pullPolicy`, and `publish` options.

| | |
|----------------------|--------------------------------------|
| Name | image |
| Type | org.springframework.boot.maven.Image |
| Default value | |
| User property | |
| Since | 2.3.0 |

includeSystemScope

Include system scoped dependencies.

| | |
|----------------------|--------------------|
| Name | includeSystemScope |
| Type | boolean |
| Default value | false |
| User property | |
| Since | 1.4.0 |

includes

Collection of artifact definitions to include. The `Include` element defines mandatory `groupId` and `artifactId` properties and an optional mandatory `groupId` and `artifactId` properties and an

optional `classifier` property.

| | |
|----------------------|-----------------------------------|
| Name | <code>includes</code> |
| Type | <code>java.util.List</code> |
| Default value | |
| User property | <code>spring-boot.includes</code> |
| Since | <code>1.2.0</code> |

layers

Layer configuration with options to disable layer creation, exclude layer tools jar, and provide a custom layers configuration file.

| | |
|----------------------|--|
| Name | <code>layers</code> |
| Type | <code>org.springframework.boot.maven.Layers</code> |
| Default value | |
| User property | |
| Since | <code>2.3.0</code> |

layout

The type of archive (which corresponds to how the dependencies are laid out inside it). Possible values are `JAR`, `WAR`, `ZIP`, `DIR`, `NONE`. Defaults to a guess based on the archive type.

| | |
|----------------------|--|
| Name | <code>layout</code> |
| Type | <code>org.springframework.boot.maven.AbstractPackagerMojo\$LayoutType</code> |
| Default value | |
| User property | |
| Since | <code>2.3.11</code> |

layoutFactory

The layout factory that will be used to create the executable archive if no explicit layout is set. Alternative layouts implementations can be provided by 3rd parties.

| | |
|----------------------|--|
| Name | <code>layoutFactory</code> |
| Type | <code>org.springframework.boot.loader.tools.LayoutFactory</code> |
| Default value | |
| User property | |
| Since | <code>2.3.11</code> |

`mainClass`

The name of the main class. If not specified the first compiled class found that contains a `main` method will be used.

| | |
|----------------------|-------------------------------|
| Name | <code>mainClass</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | |
| Since | <code>1.0.0</code> |

`skip`

Skip the execution.

| | |
|----------------------|---|
| Name | <code>skip</code> |
| Type | <code>boolean</code> |
| Default value | <code>false</code> |
| User property | <code>spring-boot.build-image.skip</code> |
| Since | <code>2.3.0</code> |

`sourceDirectory`

Directory containing the source archive.

| | |
|-------------|------------------------------|
| Name | <code>sourceDirectory</code> |
| Type | <code>java.io.File</code> |

| | |
|----------------------|--|
| Default value | <code>\${project.build.directory}</code> |
| User property | |
| Since | <code>2.3.0</code> |

6.6. Examples

6.6.1. Custom Image Builder

If you need to customize the builder used to create the image or the run image used to launch the built image, configure the plugin as shown in the following example:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <image>
            <builder>mine/java-cnb-builder</builder>
            <runImage>mine/java-cnb-run</runImage>
          </image>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

This configuration will use a builder image with the name `mine/java-cnb-builder` and the tag `latest`, and the run image named `mine/java-cnb-run` and the tag `latest`.

The builder and run image can be specified on the command line as well, as shown in this example:

```
$ mvn spring-boot:build-image -Dspring-boot.build-image.builder=mine/java-cnb-builder
-Dspring-boot.build-image.runImage=mine/java-cnb-run
```

6.6.2. Builder Configuration

If the builder exposes configuration options using environment variables, those can be set using the `env` attributes.

The following is an example of [configuring the JVM version](#) used by the Paketo Java buildpacks at build time:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <image>
            <env>
              <BP_JVM_VERSION>17</BP_JVM_VERSION>
            </env>
          </image>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```

If there is a network proxy between the Docker daemon the builder runs in and network locations that buildpacks download artifacts from, you will need to configure the builder to use the proxy. When using the Paketo builder, this can be accomplished by setting the `HTTPS_PROXY` and/or `HTTP_PROXY` environment variables as show in the following example:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <image>
            <env>
              <HTTP_PROXY>http://proxy.example.com</HTTP_PROXY>
              <HTTPS_PROXY>https://proxy.example.com</HTTPS_PROXY>
            </env>
          </image>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```

6.6.3. Runtime JVM Configuration

Paketo Java buildpacks [configure the JVM runtime environment](#) by setting the `JAVA_TOOL_OPTIONS` environment variable. The buildpack-provided `JAVA_TOOL_OPTIONS` value can be modified to customize JVM runtime behavior when the application image is launched in a container.

Environment variable modifications that should be stored in the image and applied to every deployment can be set as described in the [Paketo documentation](#) and shown in the following example:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <image>
            <env>
              <BPE_DELIM_JAVA_TOOL_OPTIONS xml:space="preserve">
</BPE_DELIM_JAVA_TOOL_OPTIONS>
              <BPE_APPEND_JAVA_TOOL_OPTIONS>-
XX:+HeapDumpOnOutOfMemoryError</BPE_APPEND_JAVA_TOOL_OPTIONS>
            </env>
          </image>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

6.6.4. Custom Image Name

By default, the image name is inferred from the `artifactId` and the `version` of the project, something like `docker.io/library/${project.artifactId}:${project.version}`. You can take control over the name, as shown in the following example:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <image>
            <name>example.com/library/${project.artifactId}</name>
          </image>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```



This configuration does not provide an explicit tag so `latest` is used. It is possible to specify a tag as well, either using `${project.version}`, any property available in the build or a hardcoded version.

The image name can be specified on the command line as well, as shown in this example:

```
$ mvn spring-boot:build-image -Dspring-boot.build
-image.imageName=example.com/library/my-app:v1
```

6.6.5. Buildpacks

By default, the builder will use buildpacks included in the builder image and apply them in a pre-defined order. An alternative set of buildpacks can be provided to apply buildpacks that are not included in the builder, or to change the order of included buildpacks. When one or more buildpacks are provided, only the specified buildpacks will be applied.

The following example instructs the builder to use a custom buildpack packaged in a `.tgz` file, followed by a buildpack included in the builder.

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <image>
            <buildpacks>
              <buildpack>file:///path/to/example-
buildpack.tgz</buildpack>
              <buildpack>urn:cnb:builder:paketo-
buildpacks/java</buildpack>
            </buildpacks>
          </image>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

Buildpacks can be specified in any of the forms shown below.

A buildpack located in a CNB Builder (version may be omitted if there is only one buildpack in the builder matching the `buildpack-id`):

- `urn:cnb:builder:buildpack-id`
- `urn:cnb:builder:buildpack-id@0.0.1`

- `buildpack-id`
- `buildpack-id@0.0.1`

A path to a directory containing buildpack content (not supported on Windows):

- `file:///path/to/buildpack/`
- `/path/to/buildpack/`

A path to a gzipped tar file containing buildpack content:

- `file:///path/to/buildpack.tgz`
- `/path/to/buildpack.tgz`

An OCI image containing a [packaged buildpack](#):

- `docker://example/buildpack`
- `docker:///example/buildpack:latest`
- `docker:///example/buildpack@sha256:45b23dee08...`
- `example/buildpack`
- `example/buildpack:latest`
- `example/buildpack@sha256:45b23dee08...`

6.6.6. Image Publishing

The generated image can be published to a Docker registry by enabling a `publish` option.

If the Docker registry requires authentication, the credentials can be configured using `docker.publishRegistry` parameters. If the Docker registry does not require authentication, the `docker.publishRegistry` configuration can be omitted.



The registry that the image will be published to is determined by the registry part of the image name (`docker.example.com` in these examples). If `docker.publishRegistry` credentials are configured and include a `url` parameter, this value is passed to the registry but is not used to determine the publishing registry location.


```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <image>
            <name>docker.example.com/library/${project.artifactId}</name>
            <publish>true</publish>
          </image>
          <docker>
            <publishRegistry>
              <username>user</username>
              <password>secret</password>
            </publishRegistry>
          </docker>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```

The **publish** option can be specified on the command line as well, as shown in this example:

```

$ mvn spring-boot:build-image -Dspring-boot.build
-image.imageName=docker.example.com/library/my-app:v1 -Dspring-boot.build
-image.publish=true

```

When using the **publish** option on the command line with authentication, you can provide credentials using properties as in this example:

```

$ mvn spring-boot:build-image \
  -Ddocker.publishRegistry.username=user \
  -Ddocker.publishRegistry.password=secret \
  -Ddocker.publishRegistry.url=docker.example.com \
  -Dspring-boot.build-image.publish=true \
  -Dspring-boot.build-image.imageName=docker.example.com/library/my-app:v1

```

and reference the properties in the XML configuration:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <docker>
            <publishRegistry>
              <url>${docker.publishRegistry.url}</url>
              <username>${docker.publishRegistry.username}</username>
              <password>${docker.publishRegistry.password}</password>
            </publishRegistry>
          </docker>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

6.6.7. Builder Cache Configuration

The CNB builder caches layers that are used when building and launching an image. By default, these caches are stored as named volumes in the Docker daemon with names that are derived from the full name of the target image. If the image name changes frequently, for example when the project version is used as a tag in the image name, then the caches can be invalidated frequently.

The cache volumes can be configured to use alternative names to give more control over cache lifecycle as shown in the following example:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <image>
            <buildCache>
              <volume>
                <name>cache-${project.artifactId}.build</name>
              </volume>
            </buildCache>
            <launchCache>
              <volume>
                <name>cache-${project.artifactId}.launch</name>
              </volume>
            </launchCache>
          </image>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```

6.6.8. Docker Configuration

Docker Configuration for minikube

The plugin can communicate with the [Docker daemon provided by minikube](#) instead of the default local connection.

On Linux and macOS, environment variables can be set using the command `eval $(minikube docker-env)` after minikube has been started.

The plugin can also be configured to use the minikube daemon by providing connection details similar to those shown in the following example:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <docker>
            <host>tcp://192.168.99.100:2376</host>
            <tlsVerify>true</tlsVerify>
            <certPath>/home/user/.minikube/certs</certPath>
          </docker>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```

Docker Configuration for podman

The plugin can communicate with a [podman container engine](#).

The plugin can be configured to use podman local connection by providing connection details similar to those shown in the following example:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <docker>
            <host>unix:///run/user/1000/podman/podman.sock</host>
            <bindHostToBuilder>true</bindHostToBuilder>
          </docker>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```



With the `colima` CLI installed, the command `podman info --format='{.Host.RemoteSocket.Path}'` can be used to get the value for the `docker.host` configuration property shown in this example.

Docker Configuration for Colima

The plugin can communicate with the Docker daemon provided by [Colima](#). The `DOCKER_HOST` environment variable can be set by using the command `export DOCKER_HOST=$(docker context inspect colima -f '{{.Endpoints.docker.Host}}')`.

The plugin can also be configured to use Colima daemon by providing connection details similar to those shown in the following example:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <docker>
            <host>unix:///${user.home}/.colima/docker.sock</host>
          </docker>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

Docker Configuration for Authentication

If the builder or run image are stored in a private Docker registry that supports user authentication, authentication details can be provided using `docker.builderRegistry` parameters as shown in the following example:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <docker>
            <builderRegistry>
              <username>user</username>
              <password>secret</password>
              <url>https://docker.example.com/v1/</url>
              <email>user@example.com</email>
            </builderRegistry>
          </docker>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```

If the builder or run image is stored in a private Docker registry that supports token authentication, the token value can be provided using `docker.builderRegistry` parameters as shown in the following example:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <docker>
            <builderRegistry>
              <token>9cbaf023786cd7...</token>
            </builderRegistry>
          </docker>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```

Chapter 7. Running your Application with Maven

The plugin includes a run goal which can be used to launch your application from the command line, as shown in the following example:

```
$ mvn spring-boot:run
```

Application arguments can be specified using the `arguments` parameter, see [using application arguments](#) for more details.

The application is executed in a forked process and setting properties on the command-line will not affect the application. If you need to specify some JVM arguments (that is for debugging purposes), you can use the `jvmArguments` parameter, see [Debug the application](#) for more details. There is also explicit support for [system properties](#) and [environment variables](#).

As enabling a profile is quite common, there is dedicated `profiles` property that offers a shortcut for `-Dspring-boot.run.jvmArguments="-Dspring.profiles.active=dev"`, see [Specify active profiles](#).

Spring Boot `devtools` is a module to improve the development-time experience when working on Spring Boot applications. To enable it, just add the following dependency to your project:

```
<dependencies>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-devtools</artifactId>
    <optional>true</optional>
  </dependency>
</dependencies>
```

When `devtools` is running, it detects change when you recompile your application and automatically refreshes it. This works for not only resources but code as well. It also provides a LiveReload server so that it can automatically trigger a browser refresh whenever things change.

Devtools can also be configured to only refresh the browser whenever a static resource has changed (and ignore any change in the code). Just include the following property in your project:

```
spring.devtools.remote.restart.enabled=false
```

Prior to `devtools`, the plugin supported hot refreshing of resources by default which has now be disabled in favour of the solution described above. You can restore it at any time by configuring your project:

```

<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
      <configuration>
        <addResources>true</addResources>
      </configuration>
    </plugin>
  </plugins>
</build>

```

When `addResources` is enabled, any `src/main/resources` directory will be added to the application classpath when you run the application and any duplicate found in `target/classes` will be removed. This allows hot refreshing of resources which can be very useful when developing web applications. For example, you can work on HTML, CSS or JavaScript files and see your changes immediately without recompiling your application. It is also a helpful way of allowing your front end developers to work without needing to download and install a Java IDE.



A side effect of using this feature is that filtering of resources at build time will not work.

In order to be consistent with the `repackage` goal, the `run` goal builds the classpath in such a way that any dependency that is excluded in the plugin's configuration gets excluded from the classpath as well. For more details, see [the dedicated example](#).

Sometimes it is useful to include test dependencies when running the application. For example, if you want to run your application in a test mode that uses stub classes. If you wish to do this, you can set the `useTestClasspath` parameter to true.



This is only applied when you run an application: the `repackage` goal will not add test dependencies to the resulting JAR/WAR.

7.1. spring-boot:run

`org.springframework.boot:spring-boot-maven-plugin:3.0.17.2`

Run an application in place.

7.1.1. Required parameters

| Name | Type | Default |
|-------------------------------|------|--|
| <code>classesDirectory</code> | File | <code>\${project.build.outputDirectory}</code> |

7.1.2. Optional parameters

| Name | Type | Default |
|--------------------------------------|-----------------------|--------------------|
| <code>addResources</code> | <code>boolean</code> | <code>false</code> |
| <code>agents</code> | <code>File[]</code> | |
| <code>arguments</code> | <code>String[]</code> | |
| <code>commandlineArguments</code> | <code>String</code> | |
| <code>directories</code> | <code>String[]</code> | |
| <code>environmentVariables</code> | <code>Map</code> | |
| <code>excludeGroupIds</code> | <code>String</code> | |
| <code>excludes</code> | <code>List</code> | |
| <code>includes</code> | <code>List</code> | |
| <code>jvmArguments</code> | <code>String</code> | |
| <code>mainClass</code> | <code>String</code> | |
| <code>noverify</code> | <code>boolean</code> | |
| <code>optimizedLaunch</code> | <code>boolean</code> | <code>true</code> |
| <code>profiles</code> | <code>String[]</code> | |
| <code>skip</code> | <code>boolean</code> | <code>false</code> |
| <code>systemPropertyVariables</code> | <code>Map</code> | |
| <code>useTestClasspath</code> | <code>Boolean</code> | <code>false</code> |
| <code>workingDirectory</code> | <code>File</code> | |

7.1.3. Parameter details

`addResources`

Add maven resources to the classpath directly, this allows live in-place editing of resources. Duplicate resources are removed from `target/classes` to prevent them from appearing twice if `ClassLoader.getResources()` is called. Please consider adding `spring-boot-devtools` to your project instead as it provides this feature and many more.

| | |
|----------------------|---|
| Name | <code>addResources</code> |
| Type | <code>boolean</code> |
| Default value | <code>false</code> |
| User property | <code>spring-boot.run.addResources</code> |
| Since | <code>1.0.0</code> |

agents

Path to agent jars.

| | |
|----------------------|------------------------|
| Name | agents |
| Type | java.io.File[] |
| Default value | |
| User property | spring-boot.run.agents |
| Since | 2.2.0 |

arguments

Arguments that should be passed to the application.

| | |
|----------------------|--------------------|
| Name | arguments |
| Type | java.lang.String[] |
| Default value | |
| User property | |
| Since | 1.0.0 |

classesDirectory

Directory containing the classes and resource files that should be packaged into the archive.

| | |
|----------------------|-----------------------------------|
| Name | classesDirectory |
| Type | java.io.File |
| Default value | \${project.build.outputDirectory} |
| User property | |
| Since | 1.0.0 |

commandlineArguments

Arguments from the command line that should be passed to the application. Use spaces to separate multiple arguments and make sure to wrap multiple values between quotes. When specified, takes precedence over #arguments.

| | |
|----------------------|--|
| Name | <code>commandLineArguments</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | <code>spring-boot.run.arguments</code> |
| Since | <code>2.2.3</code> |

`directories`

Additional directories besides the classes directory that should be added to the classpath.

| | |
|----------------------|--|
| Name | <code>directories</code> |
| Type | <code>java.lang.String[]</code> |
| Default value | |
| User property | <code>spring-boot.run.directories</code> |
| Since | <code>1.0.0</code> |

`environmentVariables`

List of Environment variables that should be associated with the forked process used to run the application.

| | |
|----------------------|-----------------------------------|
| Name | <code>environmentVariables</code> |
| Type | <code>java.util.Map</code> |
| Default value | |
| User property | |
| Since | <code>2.1.0</code> |

`excludeGroupIds`

Comma separated list of groupId names to exclude (exact match).

| | |
|-------------|-------------------------------|
| Name | <code>excludeGroupIds</code> |
| Type | <code>java.lang.String</code> |

| | |
|----------------------|--|
| Default value | |
| User property | <code>spring-boot.excludeGroupIds</code> |
| Since | <code>1.1.0</code> |

`excludes`

Collection of artifact definitions to exclude. The `Exclude` element defines mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|----------------------|-----------------------------------|
| Name | <code>excludes</code> |
| Type | <code>java.util.List</code> |
| Default value | |
| User property | <code>spring-boot.excludes</code> |
| Since | <code>1.1.0</code> |

`includes`

Collection of artifact definitions to include. The `Include` element defines mandatory `groupId` and `artifactId` properties and an optional mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|----------------------|-----------------------------------|
| Name | <code>includes</code> |
| Type | <code>java.util.List</code> |
| Default value | |
| User property | <code>spring-boot.includes</code> |
| Since | <code>1.2.0</code> |

`jvmArguments`

JVM arguments that should be associated with the forked process used to run the application. On command line, make sure to wrap multiple values between quotes.

| | |
|-------------|-------------------------------|
| Name | <code>jvmArguments</code> |
| Type | <code>java.lang.String</code> |

| | |
|----------------------|---|
| Default value | |
| User property | <code>spring-boot.run.jvmArguments</code> |
| Since | <code>1.1.0</code> |

`mainClass`

The name of the main class. If not specified the first compiled class found that contains a 'main' method will be used.

| | |
|----------------------|---|
| Name | <code>mainClass</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | <code>spring-boot.run.main-class</code> |
| Since | <code>1.0.0</code> |

`noverify`

Flag to say that the agent requires `-noverify`.

| | |
|----------------------|---------------------------------------|
| Name | <code>noverify</code> |
| Type | <code>boolean</code> |
| Default value | |
| User property | <code>spring-boot.run.noverify</code> |
| Since | <code>1.0.0</code> |

`optimizedLaunch`

Whether the JVM's launch should be optimized.

| | |
|----------------------|------------------------------|
| Name | <code>optimizedLaunch</code> |
| Type | <code>boolean</code> |
| Default value | <code>true</code> |

| | |
|----------------------|--|
| User property | <code>spring-boot.run.optimizedLaunch</code> |
| Since | <code>2.2.0</code> |

profiles

The spring profiles to activate. Convenience shortcut of specifying the 'spring.profiles.active' argument. On command line use commas to separate multiple profiles.

| | |
|----------------------|---------------------------------------|
| Name | <code>profiles</code> |
| Type | <code>java.lang.String[]</code> |
| Default value | |
| User property | <code>spring-boot.run.profiles</code> |
| Since | <code>1.3.0</code> |

skip

Skip the execution.

| | |
|----------------------|-----------------------------------|
| Name | <code>skip</code> |
| Type | <code>boolean</code> |
| Default value | <code>false</code> |
| User property | <code>spring-boot.run.skip</code> |
| Since | <code>1.3.2</code> |

systemPropertyVariables

List of JVM system properties to pass to the process.

| | |
|----------------------|--------------------------------------|
| Name | <code>systemPropertyVariables</code> |
| Type | <code>java.util.Map</code> |
| Default value | |
| User property | |
| Since | <code>2.1.0</code> |

useTestClasspath

Flag to include the test classpath when running.

| | |
|----------------------|---|
| Name | <code>useTestClasspath</code> |
| Type | <code>java.lang.Boolean</code> |
| Default value | <code>false</code> |
| User property | <code>spring-boot.run.useTestClasspath</code> |
| Since | <code>1.3.0</code> |

workingDirectory

Current working directory to use for the application. If not specified, basedir will be used.

| | |
|----------------------|---|
| Name | <code>workingDirectory</code> |
| Type | <code>java.io.File</code> |
| Default value | |
| User property | <code>spring-boot.run.workingDirectory</code> |
| Since | <code>1.5.0</code> |

7.2. Examples

7.2.1. Debug the Application

The `run` goal runs your application in a forked process. If you need to debug it, you should add the necessary JVM arguments to enable remote debugging. The following configuration suspend the process until a debugger has joined on port 5005:

```

<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <jvmArguments>
            -Xdebug
            -Xrunjdwp:transport=dt_socket,server=y,suspend=y,address=5005
          </jvmArguments>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```

These arguments can be specified on the command line as well, make sure to wrap that properly, that is:

```

$ mvn spring-boot:run -Dspring-boot.run.jvmArguments="-Xdebug
-Xrunjdwp:transport=dt_socket,server=y,suspend=y,address=5005"

```

7.2.2. Using System Properties

System properties can be specified using the `systemPropertyVariables` attribute. The following example sets `property1` to `test` and `property2` to `42`:

```

<project>
  <build>
    <properties>
      <my.value>42</my.value>
    </properties>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <systemPropertyVariables>
            <property1>test</property1>
            <property2>${my.value}</property2>
          </systemPropertyVariables>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```


If the value is empty or not defined (that is `<my-property/>`), the system property is set with an empty String as the value. Maven trims values specified in the pom, so it is not possible to specify a System property which needs to start or end with a space through this mechanism: consider using `jvmArguments` instead.

Any String typed Maven variable can be passed as system properties. Any attempt to pass any other Maven variable type (for example a `List` or a `URL` variable) will cause the variable expression to be passed literally (unevaluated).

The `jvmArguments` parameter takes precedence over system properties defined with the mechanism above. In the following example, the value for `property1` is **overridden**:

```
$ mvn spring-boot:run -Dspring-boot.run.jvmArguments="-Dproperty1=overridden"
```

7.2.3. Using Environment Variables

Environment variables can be specified using the `environmentVariables` attribute. The following example sets the 'ENV1', 'ENV2', 'ENV3', 'ENV4' env variables:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <environmentVariables>
            <ENV1>5000</ENV1>
            <ENV2>Some Text</ENV2>
            <ENV3/>
            <ENV4></ENV4>
          </environmentVariables>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

If the value is empty or not defined (that is `<MY_ENV/>`), the env variable is set with an empty String as the value. Maven trims values specified in the pom so it is not possible to specify an env variable which needs to start or end with a space.

Any String typed Maven variable can be passed as system properties. Any attempt to pass any other Maven variable type (for example a `List` or a `URL` variable) will cause the variable expression to be passed literally (unevaluated).

Environment variables defined this way take precedence over existing values.

7.2.4. Using Application Arguments

Application arguments can be specified using the `arguments` attribute. The following example sets two arguments: `property1` and `property2=42`:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <arguments>
            <argument>property1</argument>
            <argument>property2=${my.value}</argument>
          </arguments>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

On the command-line, arguments are separated by a space the same way `jvmArguments` are. If an argument contains a space, make sure to quote it. In the following example, two arguments are available: `property1` and `property2=Hello World`:

```
$ mvn spring-boot:run -Dspring-boot.run.arguments="property1 'property2=Hello World'"
```

7.2.5. Specify Active Profiles

The active profiles to use for a particular application can be specified using the `profiles` argument.

The following configuration enables the `local` and `dev` profiles:

```
<project>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <configuration>
          <profiles>
            <profile>local</profile>
            <profile>dev</profile>
          </profiles>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

The profiles to enable can be specified on the command line as well, make sure to separate them with a comma, as shown in the following example:

```
$ mvn spring-boot:run -Dspring-boot.run.profiles=local,dev
```

Chapter 8. Ahead-of-Time Processing

Spring AOT is a process that analyzes your application at build-time and generate an optimized version of it. It is a mandatory step to run a Spring `ApplicationContext` in a native image.



For an overview of GraalVM Native Images support in Spring Boot, check the [reference documentation](#).

The Spring Boot Maven plugin offers goals that can be used to perform AOT processing on both application and test code.

8.1. Processing Applications

To configure your application to use this feature, add an execution for the `process-aot` goal, as shown in the following example:

```
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <executions>
    <execution>
      <id>process-aot</id>
      <goals>
        <goal>process-aot</goal>
      </goals>
    </execution>
  </executions>
</plugin>
```

As the `BeanFactory` is fully prepared at build-time, conditions are also evaluated. This has an important difference compared to what a regular Spring Boot application does at runtime. For instance, if you want to opt-in or opt-out for certain features, you need to configure the environment used at build time to do so. The `process-aot` goal shares a number of properties with the `run` goal for that reason.

8.1.1. Using the Native Profile

If you use `spring-boot-starter-parent` as the `parent` of your project, a `native` profile can be used to streamline the steps required to build a native image.

The `native` profile configures the following:

- Execution of `process-aot` when the Spring Boot Maven Plugin is applied on a project.
- Suitable settings so that `build-image` generates a native image.
- Sensible defaults for the [Native Build Tools Maven Plugin](#), in particular:
 - Making sure the plugin uses the raw classpath, and not the main jar file as it does not

understand our repackaged jar format.

- Validate that a suitable GraalVM version is available.
- Download third-party reachability metadata.

To benefit from the `native` profile, a module that represents an application should define two plugins, as shown in the following example:

```
<plugin>
  <groupId>org.graalvm.buildtools</groupId>
  <artifactId>native-maven-plugin</artifactId>
</plugin>
<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
</plugin>
```

A single project can trigger the generation of a native image on the command-line using either [Cloud Native Buildpacks](#) or [Native Image Build Tools](#).

To use the `native` profile with a multi-modules project, you can create a customization of the `native` profile so that it invokes your preferred technique.

To bind Cloud Native Buildpacks during the `package` phase, add the following to the root POM of your multi-modules project:

```
<profile>
  <id>native</id>
  <build>
    <pluginManagement>
      <plugins>
        <plugin>
          <groupId>org.springframework.boot</groupId>
          <artifactId>spring-boot-maven-plugin</artifactId>
          <executions>
            <execution>
              <id>build-image</id>
              <goals>
                <goal>build-image-no-fork</goal>
              </goals>
            </execution>
          </executions>
        </plugin>
      </plugins>
    </pluginManagement>
  </build>
</profile>
```

The example below does the same for Native Build Tools:

```

<profile>
  <id>native</id>
  <build>
    <pluginManagement>
      <plugins>
        <plugin>
          <groupId>org.graalvm.buildtools</groupId>
          <artifactId>native-maven-plugin</artifactId>
          <executions>
            <execution>
              <id>build-image</id>
              <goals>
                <goal>compile-no-fork</goal>
              </goals>
            </execution>
          </executions>
        </plugin>
      </plugins>
    </pluginManagement>
  </build>
</profile>

```

Once the above is in place, you can build your multi-modules project and generate a native image in the relevant sub-modules, as shown in the following example:

```
$ mvn package -Pnative
```



A "relevant" sub-module is a module that represents a Spring Boot application. Such module must define the Native Build Tools and Spring Boot plugins as described above.

8.2. spring-boot:process-aot

`org.springframework.boot:spring-boot-maven-plugin:3.0.17.2`

Invoke the AOT engine on the application.

8.2.1. Required parameters

| Name | Type | Default |
|---------------------------------|------|--|
| <code>classesDirectory</code> | File | <code>\${project.build.outputDirectory}</code> |
| <code>generatedClasses</code> | File | <code>\${project.build.directory}/spring-aot/main/classes</code> |
| <code>generatedResources</code> | File | <code>\${project.build.directory}/spring-aot/main/resources</code> |

| Name | Type | Default |
|-------------------------------|-------------------|--|
| <code>generatedSources</code> | <code>File</code> | <code>\${project.build.directory}/spring-aot/main/sources</code> |

8.2.2. Optional parameters

| Name | Type | Default |
|--------------------------------------|-----------------------|--------------------|
| <code>arguments</code> | <code>String[]</code> | |
| <code>compilerArguments</code> | <code>String</code> | |
| <code>excludeGroupIds</code> | <code>String</code> | |
| <code>excludes</code> | <code>List</code> | |
| <code>includes</code> | <code>List</code> | |
| <code>jvmArguments</code> | <code>String</code> | |
| <code>mainClass</code> | <code>String</code> | |
| <code>profiles</code> | <code>String[]</code> | |
| <code>skip</code> | <code>boolean</code> | <code>false</code> |
| <code>systemPropertyVariables</code> | <code>Map</code> | |

8.2.3. Parameter details

`arguments`

Application arguments that should be taken into account for AOT processing.

| | |
|----------------------|---------------------------------|
| Name | <code>arguments</code> |
| Type | <code>java.lang.String[]</code> |
| Default value | |
| User property | |
| Since | |

`classesDirectory`

Directory containing the classes and resource files that should be packaged into the archive.

| | |
|----------------------|--|
| Name | <code>classesDirectory</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.outputDirectory}</code> |

| | |
|----------------------|--|
| User property | |
| Since | |

compilerArguments

Arguments that should be provided to the AOT compile process. On command line, make sure to wrap multiple values between quotes.

| | |
|----------------------|-----------------------------------|
| Name | compilerArguments |
| Type | java.lang.String |
| Default value | |
| User property | spring-boot.aot.compilerArguments |
| Since | |

excludeGroupIds

Comma separated list of groupId names to exclude (exact match).

| | |
|----------------------|-----------------------------|
| Name | excludeGroupIds |
| Type | java.lang.String |
| Default value | |
| User property | spring-boot.excludeGroupIds |
| Since | 1.1.0 |

excludes

Collection of artifact definitions to exclude. The **Exclude** element defines mandatory **groupId** and **artifactId** properties and an optional **classifier** property.

| | |
|----------------------|----------------------|
| Name | excludes |
| Type | java.util.List |
| Default value | |
| User property | spring-boot.excludes |

| | |
|--------------|-------|
| Since | 1.1.0 |
|--------------|-------|

`generatedClasses`

Directory containing the generated classes.

| | |
|----------------------|--|
| Name | <code>generatedClasses</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.directory}/spring-aot/main/classes</code> |
| User property | |
| Since | |

`generatedResources`

Directory containing the generated resources.

| | |
|----------------------|--|
| Name | <code>generatedResources</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.directory}/spring-aot/main/resources</code> |
| User property | |
| Since | |

`generatedSources`

Directory containing the generated sources.

| | |
|----------------------|--|
| Name | <code>generatedSources</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.directory}/spring-aot/main/sources</code> |
| User property | |
| Since | |

`includes`

Collection of artifact definitions to include. The `Include` element defines mandatory `groupId` and `artifactId` properties and an optional mandatory `groupId` and `artifactId` properties and an

optional `classifier` property.

| | |
|----------------------|-----------------------------------|
| Name | <code>includes</code> |
| Type | <code>java.util.List</code> |
| Default value | |
| User property | <code>spring-boot.includes</code> |
| Since | <code>1.2.0</code> |

`jvmArguments`

JVM arguments that should be associated with the AOT process. On command line, make sure to wrap multiple values between quotes.

| | |
|----------------------|---|
| Name | <code>jvmArguments</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | <code>spring-boot.aot.jvmArguments</code> |
| Since | |

`mainClass`

Name of the main class to use as the source for the AOT process. If not specified the first compiled class found that contains a 'main' method will be used.

| | |
|----------------------|---|
| Name | <code>mainClass</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | <code>spring-boot.aot.main-class</code> |
| Since | |

`profiles`

Spring profiles to take into account for AOT processing.

| | |
|-------------|-----------------------|
| Name | <code>profiles</code> |
|-------------|-----------------------|

| | |
|----------------------|---------------------------------|
| Type | <code>java.lang.String[]</code> |
| Default value | |
| User property | |
| Since | |

`skip`

Skip the execution.

| | |
|----------------------|-----------------------------------|
| Name | <code>skip</code> |
| Type | <code>boolean</code> |
| Default value | <code>false</code> |
| User property | <code>spring-boot.aot.skip</code> |
| Since | |

`systemPropertyVariables`

List of JVM system properties to pass to the AOT process.

| | |
|----------------------|--------------------------------------|
| Name | <code>systemPropertyVariables</code> |
| Type | <code>java.util.Map</code> |
| Default value | |
| User property | |
| Since | |

8.3. Processing Tests

The AOT engine can be applied to JUnit 5 tests that use Spring's Test Context Framework. Suitable tests are processed by the AOT engine in order to generate `ApplicationContextInitializer` code.

To configure your application to use this feature, add an execution for the `process-test-aot` goal, as shown in the following example:

```

<plugin>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-maven-plugin</artifactId>
  <executions>
    <execution>
      <id>process-test-aot</id>
      <goals>
        <goal>process-test-aot</goal>
      </goals>
    </execution>
  </executions>
</plugin>

```



If you are using `spring-boot-starter-parent`, this execution is automatically configured if you enable the `nativeTest` profile.

As with application AOT processing, the `BeanFactory` is fully prepared at build-time.

8.4. spring-boot:process-test-aot

`org.springframework.boot:spring-boot-maven-plugin:3.0.17.2`

Invoke the AOT engine on tests.

8.4.1. Required parameters

| Name | Type | Default |
|-----------------------------------|------|--|
| <code>classesDirectory</code> | File | <code>\${project.build.outputDirectory}</code> |
| <code>generatedClasses</code> | File | <code>\${project.build.directory}/spring-aot/main/classes</code> |
| <code>generatedResources</code> | File | <code>\${project.build.directory}/spring-aot/test/resources</code> |
| <code>generatedSources</code> | File | <code>\${project.build.directory}/spring-aot/test/sources</code> |
| <code>generatedTestClasses</code> | File | <code>\${project.build.directory}/spring-aot/test/classes</code> |
| <code>testClassesDirectory</code> | File | <code>\${project.build.testOutputDirectory}</code> |

8.4.2. Optional parameters

| Name | Type | Default |
|--------------------------------|--------|---------|
| <code>compilerArguments</code> | String | |
| <code>excludeGroupIds</code> | String | |
| <code>excludes</code> | List | |

| Name | Type | Default |
|--------------------------------------|---------|---------|
| <code>includes</code> | List | |
| <code>jvmArguments</code> | String | |
| <code>skip</code> | boolean | false |
| <code>systemPropertyVariables</code> | Map | |

8.4.3. Parameter details

`classesDirectory`

Directory containing the classes and resource files that should be used to run the tests.

| | |
|----------------------|--|
| Name | <code>classesDirectory</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.outputDirectory}</code> |
| User property | |
| Since | |

`compilerArguments`

Arguments that should be provided to the AOT compile process. On command line, make sure to wrap multiple values between quotes.

| | |
|----------------------|--|
| Name | <code>compilerArguments</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | <code>spring-boot.aot.compilerArguments</code> |
| Since | |

`excludeGroupIds`

Comma separated list of groupId names to exclude (exact match).

| | |
|----------------------|-------------------------------|
| Name | <code>excludeGroupIds</code> |
| Type | <code>java.lang.String</code> |
| Default value | |

| | |
|----------------------|--|
| User property | <code>spring-boot.excludeGroupIds</code> |
| Since | <code>1.1.0</code> |

`excludes`

Collection of artifact definitions to exclude. The `Exclude` element defines mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|----------------------|-----------------------------------|
| Name | <code>excludes</code> |
| Type | <code>java.util.List</code> |
| Default value | |
| User property | <code>spring-boot.excludes</code> |
| Since | <code>1.1.0</code> |

`generatedClasses`

Directory containing the generated test classes.

| | |
|----------------------|--|
| Name | <code>generatedClasses</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.directory}/spring-aot/main/classes</code> |
| User property | |
| Since | |

`generatedResources`

Directory containing the generated test resources.

| | |
|----------------------|--|
| Name | <code>generatedResources</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.directory}/spring-aot/test/resources</code> |
| User property | |
| Since | |

generatedSources

Directory containing the generated sources.

| | |
|----------------------|---|
| Name | generatedSources |
| Type | java.io.File |
| Default value | \${project.build.directory}/spring-aot/test/sources |
| User property | |
| Since | |

generatedTestClasses

Directory containing the generated test classes.

| | |
|----------------------|---|
| Name | generatedTestClasses |
| Type | java.io.File |
| Default value | \${project.build.directory}/spring-aot/test/classes |
| User property | |
| Since | |

includes

Collection of artifact definitions to include. The `Include` element defines mandatory `groupId` and `artifactId` properties and an optional mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|----------------------|----------------------|
| Name | includes |
| Type | java.util.List |
| Default value | |
| User property | spring-boot.includes |
| Since | 1.2.0 |

jvmArguments

JVM arguments that should be associated with the AOT process. On command line, make sure to wrap multiple values between quotes.

| | |
|----------------------|---|
| Name | <code>jvmArguments</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | <code>spring-boot.aot.jvmArguments</code> |
| Since | |

`skip`

Skip the execution.

| | |
|----------------------|-----------------------------------|
| Name | <code>skip</code> |
| Type | <code>boolean</code> |
| Default value | <code>false</code> |
| User property | <code>spring-boot.aot.skip</code> |
| Since | |

`systemPropertyVariables`

List of JVM system properties to pass to the AOT process.

| | |
|----------------------|--------------------------------------|
| Name | <code>systemPropertyVariables</code> |
| Type | <code>java.util.Map</code> |
| Default value | |
| User property | |
| Since | |

`testClassesDirectory`

Directory containing the classes and resource files that should be packaged into the archive.

| | |
|----------------------|--|
| Name | <code>testClassesDirectory</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.testOutputDirectory}</code> |

| | |
|-------------------------------|--|
| User propert y | |
| Since | |

Chapter 9. Running Integration Tests

While you may start your Spring Boot application very easily from your test (or test suite) itself, it may be desirable to handle that in the build itself. To make sure that the lifecycle of your Spring Boot application is properly managed around your integration tests, you can use the `start` and `stop` goals, as shown in the following example:

```
<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
      <executions>
        <execution>
          <id>pre-integration-test</id>
          <goals>
            <goal>start</goal>
          </goals>
        </execution>
        <execution>
          <id>post-integration-test</id>
          <goals>
            <goal>stop</goal>
          </goals>
        </execution>
      </executions>
    </plugin>
  </plugins>
</build>
```

Such setup can now use the [failsafe-plugin](#) to run your integration tests as you would expect.



The application is started in a separate process and JMX is used to communicate with the application. By default, the plugin uses port `9001`. If you need to configure the JMX port, see [the dedicated example](#).

You could also configure a more advanced setup to skip the integration tests when a specific property has been set, see [the dedicated example](#).

9.1. Using Failsafe Without Spring Boot's Parent POM

Spring Boot's Parent POM, `spring-boot-starter-parent`, configures Failsafe's `<classesDirectory>` to be `${project.build.outputDirectory}`. Without this configuration, which causes Failsafe to use the compiled classes rather than the repackaged jar, Failsafe cannot load your application's classes. If you are not using the parent POM, you should configure Failsafe in the same way, as shown in the following example:

```

<plugin>
  <groupId>org.apache.maven.plugins</groupId>
  <artifactId>maven-failsafe-plugin</artifactId>
  <configuration>
    <classesDirectory>${project.build.outputDirectory}</classesDirectory>
  </configuration>
</plugin>

```

9.2. spring-boot:start

`org.springframework.boot:spring-boot-maven-plugin:3.0.17.2`

Start a spring application. Contrary to the `run` goal, this does not block and allows other goals to operate on the application. This goal is typically used in integration test scenario where the application is started before a test suite and stopped after.

9.2.1. Required parameters

| Name | Type | Default |
|-------------------------------|------|--|
| <code>classesDirectory</code> | File | <code>\${project.build.outputDirectory}</code> |

9.2.2. Optional parameters

| Name | Type | Default |
|-----------------------------------|----------|---|
| <code>addResources</code> | boolean | false |
| <code>agents</code> | File[] | |
| <code>arguments</code> | String[] | |
| <code>commandlineArguments</code> | String | |
| <code>directories</code> | String[] | |
| <code>environmentVariables</code> | Map | |
| <code>excludeGroupIds</code> | String | |
| <code>excludes</code> | List | |
| <code>includes</code> | List | |
| <code>jmxName</code> | String | <code>org.springframework.boot:type=Admin,name=SpringApplication</code> |
| <code>jmxPort</code> | int | 9001 |
| <code>jvmArguments</code> | String | |
| <code>mainClass</code> | String | |
| <code>maxAttempts</code> | int | 60 |
| <code>noverify</code> | boolean | |

| Name | Type | Default |
|-------------------------|----------|---------|
| profiles | String[] | |
| skip | boolean | false |
| systemPropertyVariables | Map | |
| useTestClasspath | Boolean | false |
| wait | long | 500 |
| workingDirectory | File | |

9.2.3. Parameter details

addResources

Add maven resources to the classpath directly, this allows live in-place editing of resources. Duplicate resources are removed from `target/classes` to prevent them from appearing twice if `ClassLoader.getResources()` is called. Please consider adding `spring-boot-devtools` to your project instead as it provides this feature and many more.

| | |
|----------------------|------------------------------|
| Name | addResources |
| Type | boolean |
| Default value | false |
| User property | spring-boot.run.addResources |
| Since | 1.0.0 |

agents

Path to agent jars.

| | |
|----------------------|------------------------|
| Name | agents |
| Type | java.io.File[] |
| Default value | |
| User property | spring-boot.run.agents |
| Since | 2.2.0 |

arguments

Arguments that should be passed to the application.

| | |
|----------------------|---------------------------------|
| Name | <code>arguments</code> |
| Type | <code>java.lang.String[]</code> |
| Default value | |
| User property | |
| Since | <code>1.0.0</code> |

`classesDirectory`

Directory containing the classes and resource files that should be packaged into the archive.

| | |
|----------------------|--|
| Name | <code>classesDirectory</code> |
| Type | <code>java.io.File</code> |
| Default value | <code>\${project.build.outputDirectory}</code> |
| User property | |
| Since | <code>1.0.0</code> |

`commandlineArguments`

Arguments from the command line that should be passed to the application. Use spaces to separate multiple arguments and make sure to wrap multiple values between quotes. When specified, takes precedence over `#arguments`.

| | |
|----------------------|--|
| Name | <code>commandlineArguments</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | <code>spring-boot.run.arguments</code> |
| Since | <code>2.2.3</code> |

`directories`

Additional directories besides the classes directory that should be added to the classpath.

| | |
|-------------|---------------------------------|
| Name | <code>directories</code> |
| Type | <code>java.lang.String[]</code> |

| | |
|----------------------|--|
| Default value | |
| User property | <code>spring-boot.run.directories</code> |
| Since | <code>1.0.0</code> |

`environmentVariables`

List of Environment variables that should be associated with the forked process used to run the application.

| | |
|----------------------|-----------------------------------|
| Name | <code>environmentVariables</code> |
| Type | <code>java.util.Map</code> |
| Default value | |
| User property | |
| Since | <code>2.1.0</code> |

`excludeGroupIds`

Comma separated list of groupId names to exclude (exact match).

| | |
|----------------------|--|
| Name | <code>excludeGroupIds</code> |
| Type | <code>java.lang.String</code> |
| Default value | |
| User property | <code>spring-boot.excludeGroupIds</code> |
| Since | <code>1.1.0</code> |

`excludes`

Collection of artifact definitions to exclude. The `Exclude` element defines mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|----------------------|-----------------------------|
| Name | <code>excludes</code> |
| Type | <code>java.util.List</code> |
| Default value | |

| | |
|----------------------|-----------------------------------|
| User property | <code>spring-boot.excludes</code> |
| Since | <code>1.1.0</code> |

`includes`

Collection of artifact definitions to include. The `Include` element defines mandatory `groupId` and `artifactId` properties and an optional mandatory `groupId` and `artifactId` properties and an optional `classifier` property.

| | |
|----------------------|-----------------------------------|
| Name | <code>includes</code> |
| Type | <code>java.util.List</code> |
| Default value | |
| User property | <code>spring-boot.includes</code> |
| Since | <code>1.2.0</code> |

`jmxName`

The JMX name of the automatically deployed MBean managing the lifecycle of the spring application.

| | |
|----------------------|---|
| Name | <code>jmxName</code> |
| Type | <code>java.lang.String</code> |
| Default value | <code>org.springframework.boot:type=Admin,name=SpringApplication</code> |
| User property | |
| Since | |

`jmxPort`

The port to use to expose the platform MBeanServer.

| | |
|----------------------|----------------------|
| Name | <code>jmxPort</code> |
| Type | <code>int</code> |
| Default value | <code>9001</code> |

| | |
|----------------------|--|
| User property | |
| Since | |

jvmArguments

JVM arguments that should be associated with the forked process used to run the application. On command line, make sure to wrap multiple values between quotes.

| | |
|----------------------|------------------------------|
| Name | jvmArguments |
| Type | java.lang.String |
| Default value | |
| User property | spring-boot.run.jvmArguments |
| Since | 1.1.0 |

mainClass

The name of the main class. If not specified the first compiled class found that contains a 'main' method will be used.

| | |
|----------------------|----------------------------|
| Name | mainClass |
| Type | java.lang.String |
| Default value | |
| User property | spring-boot.run.main-class |
| Since | 1.0.0 |

maxAttempts

The maximum number of attempts to check if the spring application is ready. Combined with the "wait" argument, this gives a global timeout value (30 sec by default)

| | |
|----------------------|-------------|
| Name | maxAttempts |
| Type | int |
| Default value | 60 |

| | |
|----------------------|--|
| User property | <code>spring-boot.start.maxAttempts</code> |
| Since | |

noverify

Flag to say that the agent requires -noverify.

| | |
|----------------------|---------------------------------------|
| Name | <code>noverify</code> |
| Type | <code>boolean</code> |
| Default value | |
| User property | <code>spring-boot.run.noverify</code> |
| Since | <code>1.0.0</code> |

profiles

The spring profiles to activate. Convenience shortcut of specifying the 'spring.profiles.active' argument. On command line use commas to separate multiple profiles.

| | |
|----------------------|---------------------------------------|
| Name | <code>profiles</code> |
| Type | <code>java.lang.String[]</code> |
| Default value | |
| User property | <code>spring-boot.run.profiles</code> |
| Since | <code>1.3.0</code> |

skip

Skip the execution.

| | |
|----------------------|-----------------------------------|
| Name | <code>skip</code> |
| Type | <code>boolean</code> |
| Default value | <code>false</code> |
| User property | <code>spring-boot.run.skip</code> |
| Since | <code>1.3.2</code> |

systemPropertyVariables

List of JVM system properties to pass to the process.

| | |
|----------------------|-------------------------|
| Name | systemPropertyVariables |
| Type | java.util.Map |
| Default value | |
| User property | |
| Since | 2.1.0 |

useTestClasspath

Flag to include the test classpath when running.

| | |
|----------------------|----------------------------------|
| Name | useTestClasspath |
| Type | java.lang.Boolean |
| Default value | false |
| User property | spring-boot.run.useTestClasspath |
| Since | 1.3.0 |

wait

The number of milliseconds to wait between each attempt to check if the spring application is ready.

| | |
|----------------------|------------------------|
| Name | wait |
| Type | long |
| Default value | 500 |
| User property | spring-boot.start.wait |
| Since | |

workingDirectory

Current working directory to use for the application. If not specified, basedir will be used.

| | |
|-------------|------------------|
| Name | workingDirectory |
|-------------|------------------|

| | |
|----------------------|---|
| Type | <code>java.io.File</code> |
| Default value | |
| User property | <code>spring-boot.run.workingDirectory</code> |
| Since | <code>1.5.0</code> |

9.3. spring-boot:stop

`org.springframework.boot:spring-boot-maven-plugin:3.0.17.2`

Stop an application that has been started by the "start" goal. Typically invoked once a test suite has completed.

9.3.1. Optional parameters

| Name | Type | Default |
|----------------------|----------------------|---|
| <code>jmxName</code> | <code>String</code> | <code>org.springframework.boot:type=Admin,name=SpringApplication</code> |
| <code>jmxPort</code> | <code>int</code> | <code>9001</code> |
| <code>skip</code> | <code>boolean</code> | <code>false</code> |

9.3.2. Parameter details

`jmxName`

The JMX name of the automatically deployed MBean managing the lifecycle of the application.

| | |
|----------------------|---|
| Name | <code>jmxName</code> |
| Type | <code>java.lang.String</code> |
| Default value | <code>org.springframework.boot:type=Admin,name=SpringApplication</code> |
| User property | |
| Since | |

`jmxPort`

The port to use to look up the platform MBeanServer.

| | |
|-------------|----------------------|
| Name | <code>jmxPort</code> |
| Type | <code>int</code> |

| | |
|----------------------|------|
| Default value | 9001 |
| User property | |
| Since | |

skip

Skip the execution.

| | |
|----------------------|-----------------------|
| Name | skip |
| Type | boolean |
| Default value | false |
| User property | spring-boot.stop.skip |
| Since | 1.3.2 |

9.4. Examples

9.4.1. Random Port for Integration Tests

One nice feature of the Spring Boot test integration is that it can allocate a free port for the web application. When the `start` goal of the plugin is used, the Spring Boot application is started separately, making it difficult to pass the actual port to the integration test itself.

The example below showcases how you could achieve the same feature using the [Build Helper Maven Plugin](#):

```
<build>
  <plugins>
    <plugin>
      <groupId>org.codehaus.mojo</groupId>
      <artifactId>build-helper-maven-plugin</artifactId>
      <executions>
        <execution>
          <id>reserve-tomcat-port</id>
          <goals>
            <goal>reserve-network-port</goal>
          </goals>
          <phase>process-resources</phase>
          <configuration>
            <portNames>
              <portName>tomcat.http.port</portName>
            </portNames>
          </configuration>
        </execution>
      </executions>
    </plugin>
  </plugins>
</build>
```

```

        </portNames>
    </configuration>
</execution>
</executions>
</plugin>
<plugin>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-maven-plugin</artifactId>
    <executions>
        <execution>
            <id>pre-integration-test</id>
            <goals>
                <goal>start</goal>
            </goals>
            <configuration>
                <arguments>
                    <argument>--server.port=${tomcat.http.port}</argument>
                </arguments>
            </configuration>
        </execution>
        <execution>
            <id>post-integration-test</id>
            <goals>
                <goal>stop</goal>
            </goals>
        </execution>
    </executions>
</plugin>
<plugin>
    <groupId>org.apache.maven.plugins</groupId>
    <artifactId>maven-failsafe-plugin</artifactId>
    <configuration>
        <systemPropertyVariables>
            <test.server.port>${tomcat.http.port}</test.server.port>
        </systemPropertyVariables>
    </configuration>
</plugin>
</plugins>
</build>

```

You can now retrieve the `test.server.port` system property in any of your integration test to create a proper `URL` to the server.

9.4.2. Customize JMX port

The `jmxPort` property allows to customize the port the plugin uses to communicate with the Spring Boot application.

This example shows how you can customize the port in case `9001` is already used:

```
<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
      <configuration>
        <jmxPort>9009</jmxPort>
      </configuration>
      <executions>
        <execution>
          <id>pre-integration-test</id>
          <goals>
            <goal>start</goal>
          </goals>
        </execution>
        <execution>
          <id>post-integration-test</id>
          <goals>
            <goal>stop</goal>
          </goals>
        </execution>
      </executions>
    </plugin>
  </plugins>
</build>
```



If you need to configure the JMX port, make sure to do so in the global configuration as shown above so that it is shared by both goals.

9.4.3. Skip Integration Tests

The `skip` property allows to skip the execution of the Spring Boot maven plugin altogether.

This example shows how you can skip integration tests with a command-line property and still make sure that the `repackage` goal runs:

```

<project>
  <properties>
    <skip.it>>false</skip.it>
  </properties>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <executions>
          <execution>
            <id>pre-integration-test</id>
            <goals>
              <goal>start</goal>
            </goals>
            <configuration>
              <skip>${skip.it}</skip>
            </configuration>
          </execution>
          <execution>
            <id>post-integration-test</id>
            <goals>
              <goal>stop</goal>
            </goals>
            <configuration>
              <skip>${skip.it}</skip>
            </configuration>
          </execution>
        </executions>
      </plugin>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId>
        <artifactId>maven-failsafe-plugin</artifactId>
        <configuration>
          <skip>${skip.it}</skip>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>

```

By default, the integration tests will run but this setup allows you to easily disable them on the command-line as follows:

```
$ mvn verify -Dskip.it=true
```

Chapter 10. Integrating with Actuator

Spring Boot Actuator displays build-related information if a `META-INF/build-info.properties` file is present. The `build-info` goal generates such file with the coordinates of the project and the build time. It also allows you to add an arbitrary number of additional properties, as shown in the following example:

```
<project>
  <modelVersion>4.0.0</modelVersion>
  <artifactId>build-info</artifactId>
  <build>
    <plugins>
      <plugin>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
        <executions>
          <execution>
            <goals>
              <goal>build-info</goal>
            </goals>
            <configuration>
              <additionalProperties>
                <encoding.source>UTF-8</encoding.source>
                <encoding.reporting>UTF-8</encoding.reporting>
                <java.source>${maven.compiler.source}</java.source>
                <java.target>${maven.compiler.target}</java.target>
              </additionalProperties>
            </configuration>
          </execution>
        </executions>
      </plugin>
    </plugins>
  </build>
</project>
```

This configuration will generate a `build-info.properties` at the expected location with four additional keys.



`maven.compiler.source` and `maven.compiler.target` are expected to be regular properties available in the project. They will be interpolated as you would expect.

10.1. `spring-boot:build-info`

`org.springframework.boot:spring-boot-maven-plugin:3.0.17.2`

Generate a `build-info.properties` file based on the content of the current `MavenProject`.

10.1.1. Optional parameters

| Name | Type | Default |
|------------------------------------|--------|---|
| <code>additionalProperties</code> | Map | |
| <code>excludeInfoProperties</code> | List | |
| <code>outputFile</code> | File | <code>\${project.build.outputDirectory}/META-INF/build-info.properties</code> |
| <code>time</code> | String | <code>\${project.build.outputTimestamp}</code> |

10.1.2. Parameter details

`additionalProperties`

Additional properties to store in the `build-info.properties` file. Each entry is prefixed by `build.` in the generated `build-info.properties`.

| | |
|----------------------|-----------------------------------|
| Name | <code>additionalProperties</code> |
| Type | <code>java.util.Map</code> |
| Default value | |
| User property | |
| Since | |

`excludeInfoProperties`

Properties that should be excluded `build-info.properties` file. Can be used to exclude the standard `group`, `artifact`, `name`, `version` or `time` properties as well as items from `additionalProperties`.

| | |
|----------------------|------------------------------------|
| Name | <code>excludeInfoProperties</code> |
| Type | <code>java.util.List</code> |
| Default value | |
| User property | |
| Since | |

`outputFile`

The location of the generated `build-info.properties` file.

| | |
|-------------|-------------------------|
| Name | <code>outputFile</code> |
|-------------|-------------------------|

| | |
|----------------------|--|
| Type | java.io.File |
| Default value | \${project.build.outputDirectory}/META-INF/build-info.properties |
| User property | |
| Since | |

time

The value used for the `build.time` property in a form suitable for `Instant#parse(CharSequence)`. Defaults to `project.build.outputTimestamp` or `session.request.startTime` if the former is not set. To disable the `build.time` property entirely, use 'off' or add it to `excludeInfoProperties`.

| | |
|----------------------|-----------------------------------|
| Name | time |
| Type | java.lang.String |
| Default value | \${project.build.outputTimestamp} |
| User property | |
| Since | 2.2.0 |

Chapter 11. Help Information

The `help` goal is a standard goal that displays information on the capabilities of the plugin.

11.1. `spring-boot:help`

`org.springframework.boot:spring-boot-maven-plugin:3.0.17.2`

Display help information on `spring-boot-maven-plugin`. Call `mvn spring-boot:help -Ddetail=true -Dgoal=<goal-name>` to display parameter details.

11.1.1. Optional parameters

| Name | Type | Default |
|-------------------------|----------------------|--------------------|
| <code>detail</code> | <code>boolean</code> | <code>false</code> |
| <code>goal</code> | <code>String</code> | |
| <code>indentSize</code> | <code>int</code> | <code>2</code> |
| <code>lineLength</code> | <code>int</code> | <code>80</code> |

11.1.2. Parameter details

`detail`

If `true`, display all settable properties for each goal.

| | |
|----------------------|----------------------|
| Name | <code>detail</code> |
| Type | <code>boolean</code> |
| Default value | <code>false</code> |
| User property | <code>detail</code> |
| Since | |

`goal`

The name of the goal for which to show help. If unspecified, all goals will be displayed.

| | |
|----------------------|-------------------------------|
| Name | <code>goal</code> |
| Type | <code>java.lang.String</code> |
| Default value | |

| | |
|----------------------|------|
| User property | goal |
| Since | |

indentSize

The number of spaces per indentation level, should be positive.

| | |
|----------------------|------------|
| Name | indentSize |
| Type | int |
| Default value | 2 |
| User property | indentSize |
| Since | |

lineLength

The maximum length of a display line, should be positive.

| | |
|----------------------|------------|
| Name | lineLength |
| Type | int |
| Default value | 80 |
| User property | lineLength |
| Since | |